

Package ‘OmniPathR’

May 10, 2021

Type Package

Title OmniPath web service client and more

Version 2.99.19

Description A client for the OmniPath web service (<https://www.omnipathdb.org>) and many other resources. It also includes functions to transform and pretty print some of the downloaded data, functions to access a number of other resources such as BioPlex, ConsensusPathDB, EVEX, Gene Ontology, Guide to Pharmacology (IUPHAR/BPS), Harmonizome, HTRIdb, Human Phenotype Ontology, InWeb InBioMap, KEGG Pathway, Pathway Commons, Ramilowski et al. 2015, RegNetwork, ReMap, TF census, TRRUST and Vinayagam et al. 2011. Furthermore, OmniPathR features a close integration with the NicheNet method for ligand activity prediction from transcriptomics data, and its R implementation `nichenetr` (available only on github).

License MIT + file LICENSE

URL <https://saezlab.github.io/OmniPathR/>

BugReports <https://github.com/saezlab/OmniPathR/issues>

biocViews GraphAndNetwork, Network, Pathways, Software, ThirdPartyClient, DataImport, DataRepresentation, GeneSignaling, GeneRegulation, SystemsBiology, Transcriptomics, SingleCell, Annotation, KEGG

Encoding UTF-8

VignetteBuilder knitr

Depends R(>= 4.1)

Imports checkmate,
curl,
digest,
dplyr,
httr,
igraph,
jsonlite,
later,
logger,
magrittr,
progress,
purrr,

rappdirs,
 readr,
 readxl,
 rlang,
 stats,
 stringr,
 tibble,
 tidyr,
 tidyselect,
 tools,
 utils,
 xml2,
 yaml

Suggests BiocStyle,

dnet,
 ggplot2,
 ggraph,
 gprofiler2,
 knitr,
 mlrMBO,
 parallelMap,
 ParamHelpers,
 rmarkdown,
 smooof,
 testthat

RoxygenNote 7.1.1

R topics documented:

.omnipath_options_defaults	6
all_uniprot	6
ancestors	7
annotated_network	8
annotation_categories	9
bioplex1	9
bioplex2	10
bioplex3	11
bioplex_all	11
bioplex_hct116_1	12
bma_motif_es	13
bma_motif_vs	14
consensuspathdb_download	14
consensuspathdb_raw_table	15
descendants	16
enzsub_graph	17
evex_download	17
filter_by_resource	18
filter_intercell_network	19
find_all_paths	21
get_annotation_resources	22
get_complex_genes	23

get_complex_resources	24
get_db	24
get_enzsub_resources	25
get_interaction_resources	26
get_intercell_categories	27
get_intercell_generic_categories	27
get_intercell_resources	28
get_ontology_db	28
get_resources	29
get_signed_ptms	30
giant_component	30
go_annot_download	31
go_annot_slim	32
go_ontology_download	33
guide2pharma_download	34
harmonizome_download	35
hpo_download	35
htridb_download	36
import_all_interactions	37
import_dorothea_interactions	38
import_intercell_network	39
import_kinaseextra_interactions	42
import_ligrecextra_interactions	43
import_lncrna_mrna_interactions	45
import_mirnatarget_interactions	46
import_omnipath_annotations	47
import_omnipath_complexes	48
import_omnipath_enzsub	49
import_omnipath_interactions	50
import_omnipath_intercell	51
import_pathwayextra_interactions	53
import_post_translational_interactions	54
import_tf_mirna_interactions	55
import_tf_target_interactions	57
import_transcriptional_interactions	58
inbiomap_download	59
inbiomap_raw	60
interaction_graph	60
intercell_categories	61
intercell_consensus_filter	62
is_ontology_id	63
kegg_info	63
kegg_open	64
kegg_pathways_download	65
kegg_pathway_download	66
kegg_pathway_list	67
kegg_picture	68
kegg_process	68
load_db	69
nichenet_build_model	70
nichenet_expression_data	71
nichenet_gr_network	72

nichenet_gr_network_evex	73
nichenet_gr_network_harmonizome	74
nichenet_gr_network_htridb	75
nichenet_gr_network_omnipath	75
nichenet_gr_network_pathwaycommons	76
nichenet_gr_network_regnetwork	77
nichenet_gr_network_remap	77
nichenet_gr_network_trrust	78
nichenet_ligand_activities	79
nichenet_ligand_target_links	80
nichenet_ligand_target_matrix	81
nichenet_lr_network	82
nichenet_lr_network_guide2pharma	83
nichenet_lr_network_omnipath	84
nichenet_lr_network_ramilowski	85
nichenet_main	85
nichenet_networks	88
nichenet_optimization	89
nichenet_remove_orphan_ligands	90
nichenet_results_dir	91
nichenet_signaling_network	91
nichenet_signaling_network_cpdb	93
nichenet_signaling_network_evex	93
nichenet_signaling_network_harmonizome	94
nichenet_signaling_network_inbiomap	95
nichenet_signaling_network_omnipath	95
nichenet_signaling_network_pathwaycommons	96
nichenet_signaling_network_vinayagam	97
nichenet_test	97
nichenet_workarounds	98
obo_parser	99
OmnipathR	100
omnipath_cache_autoclean	101
omnipath_cache_clean	102
omnipath_cache_clean_db	102
omnipath_cache_download_ready	103
omnipath_cache_filter_versions	103
omnipath_cache_get	104
omnipath_cache_key	105
omnipath_cache_latest_or_new	106
omnipath_cache_latest_version	107
omnipath_cache_load	107
omnipath_cache_move_in	108
omnipath_cache_remove	110
omnipath_cache_save	111
omnipath_cache_search	112
omnipath_cache_set_ext	113
omnipath_cache_update_status	113
omnipath_cache_wipe	114
omnipath_get_config_path	115
omnipath_load_config	115
omnipath_log	116

omnipath_logfile	117
omnipath_msg	117
omnipath_reset_config	118
omnipath_save_config	119
omnipath_set_cachedir	119
omnipath_set_console_loglevel	120
omnipath_set_logfile_loglevel	121
omnipath_set_loglevel	121
omnipath_show_db	122
omnipath_unlock_cache_db	122
ontology_ensure_id	123
ontology_ensure_name	123
ontology_name_id	124
pathwaycommons_download	125
pivot_annotations	125
print_bma_motif_es	126
print_bma_motif_vs	127
print_interactions	128
print_path_es	129
print_path_vs	130
ramilowski_download	131
regnetwork_directions	131
regnetwork_download	132
relations_list_to_table	133
relations_table_to_graph	134
relations_table_to_list	134
remap_dorothea_download	135
remap_filtered	136
remap_tf_target_download	137
resources_colname	138
simplify_intercell_network	139
swap_relations	139
tfcensus_download	140
translate_ids	141
trust_download	143
uniprot_full_id_mapping_table	144
uniprot_id_mapping_table	145
unique_intercell_network	146
vinayagam_download	147
walk_ontology_tree	147
zenodo_download	149

```
.omnipath_options_defaults
```

Default values for the package options

Description

These options describe the default settings for OmnipathR so you do not need to pass these parameters at each function call. Currently the only option useful for the public web service at `omnipathdb.org` is `omnipath.license`. If you are a for-profit user set it to `commercial` to make sure all the data you download from OmniPath is legally allowed for commercial use. Otherwise just leave it as it is: `academic`. If you don't use `omnipathdb.org` but within your organization you deployed your own pypath server and want to share data with a limited availability to outside users, you may want to use a password. For this you can use the `omnipath.password` option. Also if you want the R package to work from another pypath server instead of `omnipathdb.org`, you can change the option `omnipath.url`.

Usage

```
.omnipath_options_defaults
```

Format

An object of class `list` of length 12.

```
all_uniprots
```

A table with all UniProt IDs

Description

Retrieves a table from UniProt with all proteins for a certain organism.

Usage

```
all_uniprots(fields = "id", reviewed = TRUE, organism = 9606)
```

Arguments

<code>fields</code>	Character vector of fields as defined by UniProt. For possible values please refer to https://www.uniprot.org/help/uniprotkb%5Fcolumn%5Fnames
<code>reviewed</code>	Retrieve only reviewed ('TRUE'), only unreviewed ('FALSE') or both ('NULL').
<code>organism</code>	Integer, NCBI Taxonomy ID of the organism (by default 9606 for human).

Value

Data frame (tibble) with the requested UniProt entries and fields.

Examples

```
human_swissprot_ac <- all_uniprots(fields = 'entry name')
human_swissprot_ac
# # A tibble: 20,396 x 1
#   `Entry name`
#   <chr>
# 1 OR4K3_HUMAN
# 2 O52A1_HUMAN
# 3 O2AG1_HUMAN
# 4 O10S1_HUMAN
# 5 O11G2_HUMAN
# # . with 20,386 more rows
```

ancestors

*All ancestors in the ontology tree***Description**

Starting from the selected nodes, recursively walks the ontology tree until it reaches the root. Collects all visited nodes, which are the ancestors (parents) of the starting nodes.

Usage

```
ancestors(
  terms,
  db_key = "go_basic",
  ids = TRUE,
  relations = c("is_a", "part_of", "occurs_in", "regulates", "positively_regulates",
               "negatively_regulates")
)
```

Arguments

terms	Character vector of ontology term IDs or names. A mixture of IDs and names can be provided.
db_key	Character: key to identify the ontology database. For the available keys see omnipath_show_db .
ids	Logical: whether to return IDs or term names.
relations	Character vector of ontology relation types. Only these relations will be used.

Details

Note: this function relies on the database manager, the first call might take long because of the database load process. Subsequent calls within a short period should be faster. See [get_ontology_db](#).

Value

Character vector of ontology IDs. If the input terms are all root nodes, NULL is returned. The starting nodes won't be included in the result unless some of them are ancestors of other starting nodes.

Examples

```
ancestors('GO:0005035', ids = FALSE)
# [1] "molecular_function"
# [2] "transmembrane signaling receptor activity"
# [3] "signaling receptor activity"
# [4] "molecular transducer activity"
```

annotated_network *Network interactions with annotations*

Description

Annotations are often useful in a network context, e.g. one might want to label the interacting partners by their pathway membership. This function takes a network data frame and joins an annotation data frame from both the left and the right side, so both the source and target molecular entities will be labeled by their annotations. If one entity has many annotations these will yield many rows, hence the interacting pairs won't be unique across the data frame any more. Also if one entity has really many annotations the resulting data frame might be huge, we recommend to be careful with that. Finally, if you want to do the same but with intercell annotations, there is the [import_intercell_network](#) function.

Usage

```
annotated_network(network = NULL, annot = NULL, ...)
```

Arguments

network	Behaviour depends on type: if list, will be passed as arguments to import_omnipath_interactions to obtain a network data frame; if a data frame or tibble, it will be used as a network data frame; if a character vector, will be assumed to be a set of resource names and interactions will be queried from these resources.
annot	Either the name of an annotation resource (for a list of available resources call get_annotation_resources), or an annotation data frame. If the data frame contains more than one resources, only the first one will be used.
...	Column names selected from the annotation data frame (passed to <code>dplyr::select</code> , if empty all columns will be selected.)

Value

A data frame of interactions with annotations for both interacting entities.

Examples

```
signalink_with_pathways <-
  annotated_network('SignalLink3', 'SignalLink_pathway')
```

annotation_categories *Annotation categories and resources*

Description

A full list of annotation resources, keys and values.

Usage

```
annotation_categories()
```

Value

A data frame with resource names, annotation key labels and for each key all possible values.

Examples

```
annot_cat <- annotation_categories()
annot_cat
# # A tibble: 46,307 x 3
#   source          label  value
#   <chr>          <chr>  <chr>
# 1 connectomeDB2020 role    ligand
# 2 connectomeDB2020 role    receptor
# 3 connectomeDB2020 location ECM
# 4 connectomeDB2020 location plasma membrane
# 5 connectomeDB2020 location secreted
# 6 KEGG-PC        pathway Alanine, aspartate and glutamate metabolism
# 7 KEGG-PC        pathway Amino sugar and nucleotide sugar metabolism
# 8 KEGG-PC        pathway Aminoacyl-tRNA biosynthesis
# 9 KEGG-PC        pathway Arachidonic acid metabolism
# 10 KEGG-PC       pathway Arginine and proline metabolism
```

bioplex1

Downloads the BioPlex version 1.0 interaction dataset

Description

This dataset contains ~24,000 interactions detected in HEK293T cells using 2,594 baits. More details at <https://bioplex.hms.harvard.edu/interactions.php>.

Usage

```
bioplex1()
```

Value

Data frame (tibble) with interactions.

See Also

- [bioplex2](#)
- [bioplex3](#)
- [bioplex_hct116_1](#)
- [bioplex_all](#)

Examples

```
bioplex_interactions <- bioplex1()
nrow(bioplex_interactions)
# [1] 23744
colnames(bioplex_interactions)
# [1] "GeneA"      "GeneB"      "UniprotA"   "UniprotB"
# [5] "SymbolA"    "SymbolB"    "p_wrong"    "p_no_interaction"
# [9] "p_interaction"
```

bioplex2

Downloads the BioPlex version 2.0 interaction dataset

Description

This dataset contains ~56,000 interactions detected in HEK293T cells using 5,891 baits. More details at <https://bioplex.hms.harvard.edu/interactions.php>

Usage

```
bioplex2()
```

Value

Data frame (tibble) with interactions.

See Also

- [bioplex1](#)
- [bioplex3](#)
- [bioplex_hct116_1](#)
- [bioplex_all](#)

Examples

```
bioplex_interactions <- bioplex2()
nrow(bioplex_interactions)
# [1] 56553
colnames(bioplex_interactions)
# [1] "GeneA"      "GeneB"      "UniprotA"   "UniprotB"
# [5] "SymbolA"    "SymbolB"    "p_wrong"    "p_no_interaction"
# [9] "p_interaction"
```

`bioplex3`*Downloads the BioPlex version 3.0 interaction dataset*

Description

This dataset contains ~120,000 interactions detected in HEK293T cells using 10,128 baits. More details at <https://bioplex.hms.harvard.edu/interactions.php>.

Usage

```
bioplex3()
```

Value

Data frame (tibble) with interactions.

See Also

- [bioplex1](#)
- [bioplex2](#)
- [bioplex_hct116_1](#)
- [bioplex_all](#)

Examples

```
bioplex_interactions <- bioplex3()
nrow(bioplex_interactions)
# [1] 118162
colnames(bioplex_interactions)
# [1] "GeneA"      "GeneB"      "UniprotA"   "UniprotB"
# [5] "SymbolA"    "SymbolB"    "p_wrong"    "p_no_interaction"
# [9] "p_interaction"
```

`bioplex_all`*Downloads all BioPlex interaction datasets*

Description

BioPlex provides four interaction datasets: version 1.0, 2.0, 3.0 and HCT116 version 1.0. This function downloads all of them, merges them to one data frame, removes the duplicates (based on unique pairs of UniProt IDs) and separates the isoform numbers from the UniProt IDs. More details at <https://bioplex.hms.harvard.edu/interactions.php>.

Usage

```
bioplex_all(unique = TRUE)
```

Arguments

unique Logical. Collapse the duplicate interactions into single rows or keep them as they are. In case of merging duplicate records the maximum p value will be chosen for each record.

Value

Data frame (tibble) with interactions.

See Also

- [bioplex1](#)
- [bioplex2](#)
- [bioplex3](#)
- [bioplex_hct116_1](#)

Examples

```
bioplex_interactions <- bioplex_all()
bioplex_interactions
# # A tibble: 195,538 x 11
#   UniprotA IsoformA UniprotB IsoformB GeneA GeneB SymbolA SymbolB
#   <chr>      <int> <chr>      <int> <dbl> <dbl> <chr>    <chr>
# 1 A0AV02      2 Q5K4L6      NA 84561 11000 SLC12A8 SLC27A3
# 2 A0AV02      2 Q8N5V2      NA 84561 25791 SLC12A8 NGEF
# 3 A0AV02      2 Q9H6S3      NA 84561 64787 SLC12A8 EPS8L2
# 4 A0AV96      2 000425      2 54502 10643 RBM47   IGF2BP3
# 5 A0AV96      2 000443      NA 54502  5286 RBM47   PIK3C2A
# 6 A0AV96      2 043426      NA 54502  8867 RBM47   SYNJ1
# 7 A0AV96      2 075127      NA 54502 26024 RBM47   PTC1D1
# 8 A0AV96      2 095208      2 54502 22905 RBM47   EPN2
# 9 A0AV96      2 095900      NA 54502 26995 RBM47   TRUB2
# 10 A0AV96     2 P07910      2 54502  3183 RBM47   HNRNPC
# # . with 195,528 more rows, and 3 more variables: p_wrong <dbl>,
# #   p_no_interaction <dbl>, p_interaction <dbl>
```

bioplex_hct116_1

Downloads the BioPlex HCT116 version 1.0 interaction dataset

Description

This dataset contains ~71,000 interactions detected in HCT116 cells using 5,522 baits. More details at <https://bioplex.hms.harvard.edu/interactions.php>.

Usage

```
bioplex_hct116_1()
```

Value

Data frame (tibble) with interactions.

See Also

- [bioplex1](#)
- [bioplex2](#)
- [bioplex3](#)
- [bioplex_all](#)

Examples

```
bioplex_interactions <- bioplex_hct116_1()
nrow(bioplex_interactions)
# [1] 70966
colnames(bioplex_interactions)
# [1] "GeneA"      "GeneB"      "UniprotA"   "UniprotB"
# [5] "SymbolA"    "SymbolB"    "p_wrong"    "p_no_interaction"
# [9] "p_interaction"
```

bma_motif_es

BMA motifs from a sequence of edges

Description

These motifs can be added to a BMA canvas.

Usage

```
bma_motif_es(edge_seq, G, granularity = 2)
```

Arguments

edge_seq	An igraph edge sequence.
G	An igraph graph object.
granularity	Numeric: granularity value.

Value

Character: BMA motifs as a single string.

Examples

```
interactions <- import_omnipath_interactions(resources = 'ARN')
graph <- interaction_graph(interactions)
motifs <- bma_motif_es(igraph::E(graph)[1], graph)
```

bma_motif_vs	<i>Prints a BMA motif to the screen from a sequence of nodes, which can be copy/pasted into the BMA canvas</i>
--------------	--

Description

Intended to parallel print_path_vs

Usage

```
bma_motif_vs(node_seq, G)
```

Arguments

node_seq	An igraph node sequence.
G	An igraph graph object.

Value

Character: BMA motifs as a single string.

Examples

```
interactions <- import_omnipath_interactions(resources = 'ARN')
graph <- interaction_graph(interactions)
bma_string <- bma_motif_vs(
  igraph::all_shortest_paths(
    graph,
    from = 'ULK1',
    to = 'ATG13'
  )$res,
  graph
)
```

consensuspathdb_download

Retrieves the ConsensusPathDB network

Description

Compiles a table of binary interactions from ConsensusPathDB (<http://cpdb.molgen.mpg.de/>) and translates the UniProtKB ACs to Gene Symbols.

Usage

```
consensuspathdb_download(complex_max_size = 4, min_score = 0.9)
```

Arguments

complex_max_size	Numeric: do not expand complexes with a higher number of elements than this. ConsensusPathDB does not contain conventional interactions but lists of participants, which might be members of complexes. Some records include dozens of participants and expanding them to binary interactions result thousands, sometimes hundreds of thousands of interactions from one single record. At the end, this process consumes >10GB of memory and results rather unusable data, hence it is recommended to limit the complex sizes at some low number.
min_score	Numeric: each record in ConsensusPathDB comes with a confidence score, expressing the amount of evidences. The default value, a minimum score of 0.9 retains approx. the top 30 percent of the interactions.

Value

Data frame (tibble) with interactions.

Examples

```
cpdb_data <- consensuspathdb_download(
  complex_max_size = 1,
  min_score = .99
)
nrow(cpdb_data)
# [1] 252302
colnames(cpdb_data)
# [1] "databases" "references" "uniprot_a" "confidence" "record_id"
# [6] "uniprot_b" "in_complex" "genesymbol_a" "genesymbol_b"
cpdb_data
# # A tibble: 252,302 x 9
#   databases references uniprot_a confidence record_id uniprot_b in_com
#   <chr>      <chr>      <chr>      <dbl>    <int> <chr>    <lgl>
# 1 Reactome  NA          SUMF2_HU.    1         1 SUMF1_HU. TRUE
# 2 Reactome  NA          SUMF1_HU.    1         1 SUMF2_HU. TRUE
# 3 DIP,Reac. 22210847,. STIM1_HU.    0.998     2 TRPC1_HU. TRUE
# 4 DIP,Reac. 22210847,. TRPC1_HU.    0.998     2 STIM1_HU. TRUE
# # . with 252,292 more rows, and 2 more variables: genesymbol_a <chr>,
# #   genesymbol_b <chr>
```

consensuspathdb_raw_table

Downloads interaction data from ConsensusPathDB

Description

Downloads interaction data from ConsensusPathDB

Usage

```
consensuspathdb_raw_table()
```

Value

Data frame (tibble) with interactions.

Examples

```
cpdb_raw <- consensuspathdb_raw_table()
```

descendants	<i>All descendants in the ontology tree</i>
-------------	---

Description

Starting from the selected nodes, recursively walks the ontology tree until it reaches the leaf nodes. Collects all visited nodes, which are the descendants (children) of the starting nodes.

Usage

```
descendants(
  terms,
  db_key = "go_basic",
  ids = TRUE,
  relations = c("is_a", "part_of", "occurs_in", "regulates", "positively_regulates",
    "negatively_regulates")
)
```

Arguments

terms	Character vector of ontology term IDs or names. A mixture of IDs and names can be provided.
db_key	Character: key to identify the ontology database. For the available keys see omnipath_show_db .
ids	Logical: whether to return IDs or term names.
relations	Character vector of ontology relation types. Only these relations will be used.

Details

Note: this function relies on the database manager, the first call might take long because of the database load process. Subsequent calls within a short period should be faster. See [get_ontology_db](#).

Value

Character vector of ontology IDs. If the input terms are all leaves NULL is returned. The starting nodes won't be included in the result unless some of them are descendants of other starting nodes.

Examples

```
descendants('GO:0005035', ids = FALSE)
# [1] "tumor necrosis factor-activated receptor activity"
# [2] "TRAIL receptor activity"
# [3] "TNFSF11 receptor activity"
```

enzsub_graph	<i>Enzyme-substrate graph</i>
--------------	-------------------------------

Description

Transforms the a data frame with enzyme-substrate relationships (obtained by [import_omnipath_enzsub](#)) to an igraph graph object.

Usage

```
enzsub_graph(enzsub)
```

Arguments

enzsub Data frame created by [import_omnipath_enzsub](#)

Value

An igraph directed graph object.

See Also

- [import_omnipath_enzsub](#)
- [giant_component](#)
- [find_all_paths](#)

Examples

```
enzsub <- import_omnipath_enzsub(resources = c('PhosphoSite', 'SIGNOR'))
enzsub_g <- enzsub_graph(enzsub = enzsub)
```

evex_download	<i>Interactions from the EVEX database</i>
---------------	--

Description

Downloads interactions from EVEX, a versatile text mining resource (<http://evexdb.org>). Translates the Entrez Gene IDs to Gene Symbols and combines the interactions and references into a single data frame.

Usage

```
evex_download(  
  min_confidence = NULL,  
  remove_negatives = TRUE,  
  top_confidence = NULL  
)
```

Arguments

- `min_confidence` Numeric: a threshold for confidence scores. EVEX confidence scores span roughly from -3 to 3. By providing a numeric value in this range the lower confidence interactions can be removed. If NULL no filtering performed.
- `remove_negatives` Logical: remove the records with the "negation" attribute set.
- `top_confidence` Confidence cutoff as quantile (a number between 0 and 1). If NULL no filtering performed.

Value

Data frame (tibble) with interactions.

Examples

```
evex_interactions <- evex_download()
evex_interactions
# # A tibble: 368,297 x 13
#   general_event_id source_entrezge. target_entrezge. confidence negation
#   <dbl> <chr>           <chr>           <dbl> <dbl>
# 1      98 8651           6774             -1.45     0
# 2     100 8431           6774             -1.45     0
# 3     205 6261           6263              0.370     0
# 4     435 1044           1045             -1.09     0
# . with 368,287 more rows, and 8 more variables: speculation <dbl>,
#   coarse_type <chr>, coarse_polarity <chr>, refined_type <chr>,
#   refined_polarity <chr>, source_genesymbol <chr>,
#   target_genesymbol <chr>, references <chr>
```

`filter_by_resource` *Filters OmniPath data by resources*

Description

Keeps only those records which are supported by any of the resources of interest.

Usage

```
filter_by_resource(data, resources = NULL)
```

Arguments

- `data` A data frame downloaded from the OmniPath web service (interactions, enzyme-substrate or complexes).
- `resources` Character vector with resource names to keep.

Value

The data frame filtered.

Examples

```
interactions <- import_omnipath_interactions()
signor <- filter_by_resource(interactions, resources = 'SIGNOR')
```

```
filter_intercell_network
```

Quality filter an intercell network

Description

The intercell database of OmniPath covers a very broad range of possible ways of cell to cell communication, and the pieces of information, such as localization, topology, function and interaction, are combined from many, often independent sources. This unavoidably result some weird and unexpected combinations which are false positives in the context of intercellular communication. [import_intercell_network](#) provides a shortcut (high_confidence) to do basic quality filtering. For custom filtering or experimentation with the parameters we offer this function.

Usage

```
filter_intercell_network(
  network,
  transmitter_topology = c("secreted", "plasma_membrane_transmembrane",
    "plasma_membrane_peripheral"),
  receiver_topology = "plasma_membrane_transmembrane",
  min_curation_effort = 2,
  min_resources = 1,
  min_references = 0,
  min_provenances = 1,
  consensus_percentile = 50,
  loc_consensus_percentile = 30,
  ligand_receptor = FALSE,
  simplify = FALSE,
  unique_pairs = FALSE,
  omnipath = TRUE,
  ligreextra = TRUE,
  kinaseextra = FALSE,
  pathwayextra = FALSE,
  ...
)
```

Arguments

network	An intercell network data frame, as provided by import_intercell_network , without simplify.
transmitter_topology	Character vector: topologies allowed for the entities in transmitter role. Abbreviations allowed: "sec", "pmtm" and "pmp".
receiver_topology	Same as transmitter_topology for the entities in the receiver role.

min_curation_effort	Numeric: a minimum value of curation effort (resource-reference pairs) for network interactions. Use zero to disable filtering.
min_resources	Numeric: minimum number of resources for interactions. The value 1 means no filtering.
min_references	Numeric: minimum number of references for interactions. Use zero to disable filtering.
min_provenances	Numeric: minimum number of provenances (either resources or references) for interactions. Use zero or one to disable filtering.
consensus_percentile	Numeric: percentile threshold for the consensus score of generic categories in intercell annotations. The consensus score is the number of resources supporting the classification of an entity into a category based on combined information of many resources. Here you can apply a cut-off, keeping only the annotations supported by a higher number of resources than a certain percentile of each category. If NULL no filtering will be performed. The value is either in the 0-1 range, or will be divided by 100 if greater than 1. The percentiles will be calculated against the generic composite categories and then will be applied to their resource specific annotations and specific child categories.
loc_consensus_percentile	Numeric: similar to consensus_percentile for major localizations. For example, with a value of 50, the secreted, plasma membrane transmembrane or peripheral attributes will be TRUE only where at least 50 percent of the resources support these.
ligand_receptor	Logical. If TRUE, only <i>ligand</i> and <i>receptor</i> annotations will be used instead of the more generic <i>transmitter</i> and <i>receiver</i> categories.
simplify	Logical: keep only the most often used columns. This function combines a network data frame with two copies of the intercell annotation data frames, all of them already having quite some columns. With this option we keep only the names of the interacting pair, their intercellular communication roles, and the minimal information of the origin of both the interaction and the annotations.
unique_pairs	Logical: instead of having separate rows for each pair of annotations, drop the annotations and reduce the data frame to unique interacting pairs. See unique_intercell_network for details.
omnipath	Logical: shortcut to include the <i>omnipath</i> dataset in the interactions query.
ligreextra	Logical: shortcut to include the <i>ligreextra</i> dataset in the interactions query.
kinaseextra	Logical: shortcut to include the <i>kinaseextra</i> dataset in the interactions query.
pathwayextra	Logical: shortcut to include the <i>pathwayextra</i> dataset in the interactions query.
...	If simplify or unique_pairs is TRUE, additional column names can be passed here to <code>dplyr::select</code> on the final data frame. Otherwise ignored.

Value

An intercell network data frame filtered.

See Also

- [import_intercell_network](#)
- [unique_intercell_network](#)
- [simplify_intercell_network](#)

Examples

```
icn <- import_intercell_network()
icn_f <- filter_intercell_network(
  icn,
  consensus_percentile = 75,
  min_provenances = 3,
  simplify = TRUE
)
```

find_all_paths

All paths between two groups of vertices

Description

Finds all paths up to length ‘maxlen’ between specified groups of vertices. This function is needed only because igraph’s ‘all_shortest_paths’ finds only the shortest, not any path up to a defined length.

Usage

```
find_all_paths(
  graph,
  start,
  end,
  attr = NULL,
  mode = 'OUT',
  maxlen = 2,
  progress = TRUE
)
```

Arguments

graph	An igraph graph object.
start	Integer or character vector with the indices or names of one or more start vertices.
end	Integer or character vector with the indices or names of one or more end vertices.
attr	Character: name of the vertex attribute to identify the vertices by. Necessary if ‘start’ and ‘end’ are not igraph vertex ids but for example vertex names or labels.
mode	Character: IN, OUT or ALL. Default is OUT.
maxlen	Integer: maximum length of paths in steps, i.e. if maxlen = 3, then the longest path may consist of 3 edges and 4 nodes.
progress	Logical: show a progress bar. Default is FALSE.

Value

List of vertex paths, each path is a character or integer vector.

See Also

- [interaction_graph](#)
- [enzsub_graph](#)
- [giant_component](#)

Examples

```
interactions <- import_omnipath_interactions()
graph <- interaction_graph(interactions)
paths <- find_all_paths(
  graph = graph,
  start = c('EGFR', 'STAT3'),
  end = c('AKT1', 'ULK1'),
  attr = 'name'
)
```

get_annotation_resources

Retrieves a list of available resources in the annotations database of OmniPath

Description

Get the names of the resources from <https://omnipath.org/annotations>.

Usage

```
get_annotation_resources(dataset = NULL, ...)
```

Arguments

dataset	ignored for this query type
...	optional additional arguments

Value

character vector with the names of the annotation resources

See Also

- [get_resources](#)
- [import_omnipath_annotations](#)

Examples

```
get_annotation_resources()
```

get_complex_genes	<i>Get all the molecular complexes for a given gene(s)</i>
-------------------	--

Description

This function returns all the molecular complexes where an input set of genes participate. User can choose to retrieve every complex where any of the input genes participate or just retrieve these complexes where all the genes in input set participate together.

Usage

```
get_complex_genes(  
  complexes = import_omnipath_complexes(),  
  select_genes,  
  total_match = FALSE  
)
```

Arguments

complexes	complexes data frame (obtained using import_omnipath_complexes)
select_genes	vector containing the genes for whom complexes will be retrieved (hgnc format).
total_match	[default=FALSE] logical indicating if the user wants to get all the complexes where any of the input genes participate (FALSE) or to get only the complexes where all the input genes participate together (TRUE).

Value

Data frame of complexes

See Also

[import_omnipath_complexes](#)

Examples

```
complexes <- import_omnipath_complexes(  
  filter_databases = c("CORUM", "hu.MAP")  
)  
query_genes <- c("LMNA", "BANF1")  
complexes_query_genes <- get_complex_genes(complexes, query_genes)
```

`get_complex_resources` *Retrieve a list of complex resources available in Omnipath*

Description

Get the names of the resources from <https://omnipath.org/complexes>

Usage

```
get_complex_resources(dataset = NULL)
```

Arguments

`dataset` ignored for this query type

Value

character vector with the names of the databases

See Also

- [get_resources](#)
- [import_omnipath_complexes](#)

Examples

```
get_complex_resources()
```

`get_db` *Access a built in database*

Description

Databases are resources which might be costly to load but can be used many times by functions which usually automatically load and retrieve them from the database manager. Each database has a lifetime and will be unloaded automatically upon expiry.

Usage

```
get_db(key, param = NULL, reload = FALSE)
```


Arguments

key	Character: the key of the database to load. For a list of available keys see omnipath_show_db .
param	List: override the defaults or pass further parameters to the database loader function. See the loader functions and their default parameters in omnipath_show_db . If the database is already loaded with different parameters it will be reloaded with the new parameters only if the reload option is TRUE.
reload	Reload the database if param passed here is different from the parameters used the last time the database was loaded. If different functions with different parameters access the database repeatedly and request reload the frequent reloads might cost substantial time and resource use.

Value

An object with the database contents. The exact format depends on the database, most often it is a data frame or a list.

See Also

[omnipath_show_db](#).

Examples

```
goslim <- get_db('go_slim')
```

get_enzsub_resources *Retrieves a list of enzyme-substrate resources available in OmniPath*

Description

Get the names of the enzyme-substrate relationship resources available in <https://omnipath.org/enzsub>

Usage

```
get_enzsub_resources(dataset = NULL)
```

Arguments

dataset ignored for this query type

Value

character vector with the names of the enzyme-substrate resources

See Also

- [get_resources](#)
- [import_omnipath_enzsub](#)

Examples

```
get_enzsub_resources()
```

```
get_interaction_resources
```

Retrieve a list of interaction resources available in Omnipath

Description

Gets the names of the resources from <https://omnipath.org/interactions>.

Usage

```
get_interaction_resources(dataset = NULL)
```

Arguments

`dataset` a dataset within the interactions query type. Currently available datasets are 'omnipath', 'kinaseextra', 'pathwayextra', 'ligreextra', 'dorothea', 'tf_target', 'tf_mirna', 'mirnatarget' and 'lncrna_mrna'

Value

character vector with the names of the interaction databases

See Also

- [get_resources](#)
- [import_all_interactions](#)
- [import_omnipath_interactions](#)
- [import_pathwayextra_interactions](#)
- [import_kinaseextra_interactions](#)
- [import_ligreextra_interactions](#)
- [import_mirnatarget_interactions](#)
- [import_dorothea_interactions](#)

Examples

```
get_interaction_resources()
```

`get_intercell_categories`

Categories in the intercell database of OmniPath

Description

Retrieves a list of categories from <https://omnipath.org/intercell>.

Usage

```
get_intercell_categories()
```

Value

character vector with the different intercell categories

See Also

- [import_omnipath_intercell](#)
- [get_intercell_generic_categories](#)

Examples

```
get_intercell_categories()
```

`get_intercell_generic_categories`

Retrieves a list of the generic categories in the intercell database of OmniPath

Description

Retrieves a list of the generic categories from <https://omnipath.org/intercell>.

Usage

```
get_intercell_generic_categories()
```

Value

character vector with the different intercell main classes

See Also

- [import_omnipath_intercell](#)
- [get_intercell_categories](#)

Examples

```
get_intercell_generic_categories()
```

```
get_intercell_resources
```

Retrieves a list of intercellular communication resources available in OmniPath

Description

Retrieves a list of the databases from <https://omnipath.org/intercell>.

Usage

```
get_intercell_resources(dataset = NULL)
```

Arguments

dataset ignored at this query type

Value

character vector with the names of the databases

See Also

- [get_resources](#)
- [import_omnipath_intercell](#)

Examples

```
get_intercell_resources()
```

```
get_ontology_db
```

Access an ontology database

Description

Retrieves an ontology database with relations in the desired data structure. The database is automatically loaded and the requested data structure is constructed if necessary. The databases stay loaded up to a certain time period (see the option `omnipath.db_lifetime`). Hence the first one of repeated calls to this function might take long and the subsequent ones should be really quick.

Usage

```
get_ontology_db(key, rel_fmt = "tbl", child_parents = TRUE)
```

Arguments

key Character: key of the ontology database. For the available keys see [omnipath_show_db](#).

rel_fmt Character: the data structure of the ontology relations. Possible values are 1) "tbl" a data frame, 2) "lst" a list or 3) "gra" a graph.

child_parents Logical: whether the ontology relations should point from child to parents (TRUE) or from parent to children (FALSE).

Value

A list with the following elements: 1) "names" a table with term IDs and names; 2) "namespaces" a table to connect term IDs and namespaces they belong to; 3) "relations" a table with relations between terms and their parent terms; 4) "subsets" a table with terms and the subsets they are part of; 5) "obsolete" character vector with all the terms labeled as obsolete.

See Also

- [omnipath_show_db](#)
- [get_db](#)

Examples

```
go <- get_ontology_db('go_basic', child_parents = FALSE)
```

get_resources

Retrieve the available resources for a given query type

Description

Collects the names of the resources available in OmniPath for a certain query type and optionally for a dataset within that.

Usage

```
get_resources(query_type, datasets = NULL, generic_categories = NULL)
```

Arguments

query_type	one of the query types 'interactions', 'enz_sub', 'complexes', 'annotations' or 'intercell'
datasets	currently within the 'interactions' query type only, multiple datasets are available: 'omnipath', 'kinaseextra', 'pathwayextra', 'ligreextra', 'dorothea', 'tf_target', 'tf_mirna', 'mirnatarget' and 'lncrna_mrna'.
generic_categories	for the 'intercell' query type, restrict the search for some generic categories e.g. 'ligand' or 'receptor'.

Value

a character vector with resource names

Examples

```
get_resources(query_type = 'interactions')
```

get_signed_ptms *Signs for enzyme-substrate interactions*

Description

Enzyme-substrate data does not contain sign (activation/inhibition), we generate this information based on the interaction network.

Usage

```
get_signed_ptms(  
  enzsub = import_omnipath_enzsub(),  
  interactions = import_omnipath_interactions()  
)
```

Arguments

enzsub Enzyme-substrate data frame generated by [import_omnipath_enzsub](#)
interactions interaction data frame generated by [import_omnipath_interactions](#)

Value

Data frame of enzyme-substrate relationships with `is_inhibition` and `is_stimulation` columns.

See Also

- [import_omnipath_enzsub](#)
- [import_omnipath_interactions](#)

Examples

```
enzsub <- import_omnipath_enzsub(resources = c('PhosphoSite', 'SIGNOR'))  
interactions <- import_omnipath_interactions()  
enzsub <- get_signed_ptms(enzsub, interactions)
```

giant_component *Giant component of a graph*

Description

For an igraph graph object returns its giant component.

Usage

```
giant_component(graph)
```

Arguments

graph An igraph graph object.

Value

An igraph graph object containing only the giant component.

Examples

```
interactions <- import_post_translational_interactions()
graph <- interaction_graph(interactions)
graph_gc <- giant_component(graph)
```

go_annot_download *Gene annotations from Gene Ontology*

Description

Gene Ontology is an ontology of gene subcellular localizations, molecular functions and involvement in biological processes. Gene products across many organisms are annotated with the ontology terms. This function downloads the gene-ontology term associations for certain model organisms or all organisms. For a description of the columns see <http://geneontology.org/docs/go-annotation-file-gaf-format-2.2/>.

Usage

```
go_annot_download(organism = "human", aspects = c("C", "F", "P"), slim = NULL)
```

Arguments

organism	Character: either "chicken", "cow", "dog", "human", "pig" or "uniprot_all".
aspects	Character vector with some of the following elements: "C" (cellular component), "F" (molecular function) and "P" (biological process). Gene Ontology is three separate ontologies called as three aspects. By this parameter you can control which aspects to include in the output.
slim	Character: if not NULL, the name of a GOsubset (slim). instead of the full GO annotation, the slim annotation will be returned. See details at go_annot_slim . If TRUE, the "generic" slim will be used.

Value

A tibble (data frame) of annotations as it is provided by the database

Examples

```
goa_data <- go_annot_download()
goa_data
# # A tibble: 606,840 x 7
#   db          db_object_id db_object_symbol qualifier go_id    db_ref
#   <fct>      <chr>         <chr>           <fct>    <chr>  <chr>
# 1 UniProt. A0A024RBG1  NUDT4B          NA        GO:000. GO_REF:00.
# 2 UniProt. A0A024RBG1  NUDT4B          NA        GO:000. GO_REF:00.
# 3 UniProt. A0A024RBG1  NUDT4B          NA        GO:004. GO_REF:00.
# 4 UniProt. A0A024RBG1  NUDT4B          NA        GO:005. GO_REF:00.
# 5 UniProt. A0A024RBG1  NUDT4B          NA        GO:005. GO_REF:00.
```

```
## . with 606,830 more rows, and 11 more variables:
##   evidence_code <fct>, with_or_from <chr>, aspect <fct>,
##   db_object_name <chr>, db_object_synonym <chr>,
##   db_object_type <fct>, taxon <fct>, date <date>,
##   assigned_by <fct>, annotation_extension <chr>,
##   gene_product_from_id <chr>
```

go_annot_slim

GO slim gene annotations

Description

GO slims are subsets of the full GO which "give a broad overview of the ontology content without the detail of the specific fine grained terms". In order to annotate genes with GO slim terms, we take the annotations and search all ancestors of the terms up to the root of the ontology tree. From the ancestors we select the terms which are part of the slim subset.

Usage

```
go_annot_slim(
  organism = "human",
  slim = "generic",
  aspects = c("C", "F", "P"),
  cache = TRUE
)
```

Arguments

organism	Character: either "chicken", "cow", "dog", "human", "pig" or "uniprot_all".
slim	Character: the GO subset (GO slim) name. Available GO slims are: "agr" (Alliance for Genomics Resources), "generic", "aspergillus", "candida", "drosophila", "chembl", "metagenomic", "mouse", "plant", "pir" (Protein Information Resource), "pombe" and "yeast".
aspects	Character vector with some of the following elements: "C" (cellular component), "F" (molecular function) and "P" (biological process). Gene Ontology is three separate ontologies called as three aspects. By this parameter you can control which aspects to include in the output.
cache	Logical: Load the result from cache if available.

Details

Building the GO slim is resource intensive in its current implementation. For human annotation and generic GO slim it might take around 20 minutes. The result is saved into the cache so next time loading the data from there is really quick. If the cache option is FALSE the data will be built fresh (the annotation and ontology files still might come from cache), and the newly build GO slim will overwrite the cache instance.

Value

A tibble (data frame) of genes annotated with ontology terms in in the GO slim (subset).

See Also

- [go_annot_download](#)
- [go_ontology_download](#)
- [get_db](#)

Examples

```
goslim <- go_annot_slim(organism = 'human', slim = 'generic')
goslim
# # A tibble: 276,371 x 8
#   db      db_object_id db_object_symbol go_id aspect db_object_name
#   <fct> <chr>          <chr>          <chr> <fct> <chr>
# 1 UniPr. A0A024RBG1  NUDT4B          GO:0. F      Diphosphoinosito.
# 2 UniPr. A0A024RBG1  NUDT4B          GO:0. F      Diphosphoinosito.
# 3 UniPr. A0A024RBG1  NUDT4B          GO:0. C      Diphosphoinosito.
# 4 UniPr. A0A024RBG1  NUDT4B          GO:0. C      Diphosphoinosito.
# 5 UniPr. A0A024RBG1  NUDT4B          GO:0. C      Diphosphoinosito.
# # . with 276,366 more rows, and 2 more variables:
# #   db_object_synonym <chr>, db_object_type <fct>
```

go_ontology_download *The Gene Ontology tree*

Description

The Gene Ontology tree

Usage

```
go_ontology_download(
  basic = TRUE,
  tables = TRUE,
  subset = NULL,
  relations = c("is_a", "part_of", "occurs_in", "regulates", "positively_regulates",
    "negatively_regulates")
)
```

Arguments

- | | |
|--------|---|
| basic | Logical: use the basic or the full version of GO. As written on the GO home page: "the basic version of the GO is filtered such that the graph is guaranteed to be acyclic and annotations can be propagated up the graph. The relations included are is a, part of, regulates, negatively regulates and positively regulates. This version excludes relationships that cross the 3 GO hierarchies. This version should be used with most GO-based annotation tools." |
| tables | In the result return data frames or nested lists. These later can be converted to each other if necessary. However converting from table to list is faster. |

subset	Character: the GO subset (GO slim) name. GO slims are subsets of the full GO which "give a broad overview of the ontology content without the detail of the specific fine grained terms". This option, if not NULL, overrides the basic parameter. Available GO slims are: "agr" (Alliance for Genomics Resources), "generic", "aspergillus", "candida", "drosophila", "chembl", "metagenomic", "mouse", "plant", "pir" (Protein Information Resource), "pombe" and "yeast".
relations	Character vector: the relations to include in the processed data.

Value

A list with the following elements: 1) "names" a list with terms as names and names as values; 2) "namespaces" a list with terms as names and namespaces as values; 3) "relations" a list with relations between terms: terms are keys, values are lists with relations as names and character vectors of related terms as values; 4) "subsets" a list with terms as keys and character vectors of subset names as values (or NULL if the term does not belong to any subset); 5) "obsolete" character vector with all the terms labeled as obsolete. If the tables parameter is TRUE, "names", "namespaces", "relations" and "subsets" will be data frames (tibbles).

Examples

```
# retrieve the generic GO slim, a small subset of the full ontology
go <- go_ontology_download(subset = 'generic')
```

guide2pharma_download *Downloads interactions from the Guide to Pharmacology database*

Description

Downloads ligand-receptor interactions from the Guide to Pharmacology (IUPHAR/BPS) database (<https://www.guidetopharmacology.org/>).

Usage

```
guide2pharma_download()
```

Value

A tibble (data frame) of interactions as it is provided by the database

Examples

```
g2p_data <- guide2pharma_download()
g2p_data
# # A tibble: 21,586 x 38
#   target target_id target_gene_sym. target_uniprot target_ensembl_..
#   <chr>      <dbl> <chr>                <chr>          <chr>
# 1 12S-L.      1387 ALOX12                P18054         ENSG00000108839
# 2 15-LO.      1388 ALOX15                P16050         ENSG00000161905
# 3 15-LO.      1388 ALOX15                P16050         ENSG00000161905
# 4 15-LO.      1388 ALOX15                P16050         ENSG00000161905
# # . with 21,576 more rows, and 33 more variables: target_ligand <chr>,
```

```
# # target_ligand_id <chr>, target_ligand_gene_symbol <chr>,
# ... (truncated)
```

harmonizome_download *Downloads a Harmonizome network dataset*

Description

Downloads a single network dataset from Harmonizome <https://maayanlab.cloud/Harmonizome>.

Usage

```
harmonizome_download(dataset)
```

Arguments

dataset The dataset part of the URL. Please refer to the download section of the Harmonizome webpage.

Value

Data frame (tibble) with interactions.

Examples

```
harmonizome_data <- harmonizome_download('phosphositeplus')
harmonizome_data
# # A tibble: 6,013 x 7
#   source source_desc source_id target target_desc target_id weight
#   <chr>   <chr>         <dbl> <chr> <chr>         <dbl> <dbl>
# 1 TP53    na              7157 STK17A na           9263    1
# 2 TP53    na              7157 TP53RK na          112858  1
# 3 TP53    na              7157 SMG1  na           23049  1
# 4 UPF1    na              5976 SMG1  na           23049  1
# # . with 6,003 more rows
```

hpo_download *Downloads protein annotations from Human Phenotype Ontology*

Description

Human Phenotype Ontology (HPO) provides a standardized vocabulary of phenotypic abnormalities encountered in human disease. Each term in the HPO describes a phenotypic abnormality. HPO currently contains over 13,000 terms and over 156,000 annotations to hereditary diseases. See more at <https://hpo.jax.org/app/>.

Usage

```
hpo_download()
```

Value

A tibble (data frame) of annotations as it is provided by the database

Examples

```
hpo_data <- hpo_download()
hpo_data
# # A tibble: 231,738 x 9
#   entrez_gene_id entrez_gene_symb. hpo_term_id hpo_term_name
#   <dbl> <chr> <chr> <chr>
# 1     8192 CLPP      HP:0000013 Hypoplasia of the ute.
# 2     8192 CLPP      HP:0004322 Short stature
# 3     8192 CLPP      HP:0000786 Primary amenorrhea
# 4     8192 CLPP      HP:0000007 Autosomal recessive i.
# 5     8192 CLPP      HP:0000815 Hypergonadotropic hyp.
# # . with 231,733 more rows, and 5 more variables:
# #   frequency_raw <chr>, frequency_hpo <chr>, info_gd_source <chr>,
# #   gd_source <chr>, disease_id <chr>
```

htridb_download

Downloads TF-target interactions from HTRIdb

Description

HTRIdb (<https://www.lbbc.ibb.unesp.br/htri/>) is a database of literature curated human TF-target interactions. As the database is recently offline, the data is distributed by the OmniPath rescued data repository (<https://rescued.omnipathdb.org/>).

Usage

```
htridb_download()
```

Value

Data frame (tibble) with interactions.

Examples

```
htridb_data <- htridb_download()
htridb_data
# # A tibble: 18,630 x 7
#   OID GENEID_TF SYMBOL_TF GENEID_TG SYMBOL_TG TECHNIQUE
#   <dbl> <dbl> <chr> <dbl> <chr> <chr>
# 1 32399 142 PARP1 675 BRCA2 Electrophoretic Mobi.
# 2 32399 142 PARP1 675 BRCA2 Chromatin Immunoprec.
# 3 28907 196 AHR 1543 CYP1A1 Chromatin Immunoprec.
# 4 29466 196 AHR 1543 CYP1A1 Electrophoretic Mobi.
# 5 28911 196 AHR 1543 CYP1A1 Chromatin Immunoprec.
# # . with 18,620 more rows, and 1 more variable: PUBMED_ID <chr>
```

```
import_all_interactions
```

Imports all interaction datasets available in OmniPath

Description

The interaction datasets currently available in OmniPath:

Usage

```
import_all_interactions(
  resources = NULL,
  organism = 9606,
  dorothea_levels = c("A", "B"),
  exclude = NULL,
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  ...
)

import_AllInteractions(...)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
dorothea_levels	The confidence levels of the dorothea interactions (TF-target) which range from A to D. Set to A and B by default.
exclude	Character: datasets or resources to exclude.
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
...	Passed to <code>import_all_interactions</code> .

Details

omnipath: the OmniPath data as defined in the paper, an arbitrary optimum between coverage and quality
 pathwayextra: activity flow interactions without literature reference
 kinaseextra: enzyme-substrate interactions without literature reference
 ligreextra: ligand-receptor interactions without literature reference
 dorothea: transcription factor (TF)-target interactions from DoRoThEA
 tf_target: transcription factor (TF)-target interactions from other resources
 mirnatarget: miRNA-mRNA interactions
 tf_mirna: TF-miRNA interactions
 lncrna_mrna: lncRNA-mRNA interactions

Value

A dataframe containing all the datasets in the interactions query

See Also

- [get_interaction_resources](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <- import_all_interactions(
  resources = c('HPRD', 'BioGRID'),
  organism = 9606
)
```

```
import_dorothea_interactions
```

From the OmniPath webservice imports interactions from the DoRothEA dataset

Description

Imports the dataset from: <https://omnipathdb.org/interactions?datasets=dorothea> which contains transcription factor (TF)-target interactions from DoRothEA <https://github.com/saezlab/DoRothEA>

Usage

```
import_dorothea_interactions(
  resources = NULL,
  organism = 9606,
  dorothea_levels = c("A", "B"),
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
dorothea_levels	Vector detailing the confidence levels of the interactions to be downloaded. In dorothea, every TF-target interaction has a confidence score ranging from A to E, being A the most reliable interactions. By default we take A and B level interactions (c(A,B)). It is to note that E interactions are not available in OmnipathR.

fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	optional additional arguments

Value

A dataframe containing TF-target interactions from DoRothea

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <- import_dorothea_interactions(
  resources = c('DoRothea', 'ARACNe-GTEX_DoRothea'),
  organism = 9606,
  dorothea_levels = c('A', 'B', 'C')
)
```

import_intercell_network

Intercellular communication network

Description

Imports an intercellular network by combining intercellular annotations and protein interactions. First imports a network of protein-protein interactions. Then, it retrieves annotations about the proteins intercellular communication roles, once for the transmitter (delivering information from the expressing cell) and second, the receiver (receiving signal and relaying it towards the expressing cell) side. These 3 queries can be customized by providing parameters in lists which will be passed to the respective methods ([import_omnipath_interactions](#) for the network and [import_omnipath_intercell](#) for the annotations). Finally the 3 data frames combined in a way that the source proteins in each interaction annotated by the transmitter, and the target proteins by the receiver categories. If undirected interactions present (these are disabled by default) they will be duplicated, i.e. both partners can be both receiver and transmitter.

Usage

```
import_intercell_network(
  interactions_param = list(),
  transmitter_param = list(),
  receiver_param = list(),
  resources = NULL,
  entity_types = NULL,
  ligand_receptor = FALSE,
  high_confidence = FALSE,
  simplify = FALSE,
  unique_pairs = FALSE,
  consensus_percentile = NULL,
  loc_consensus_percentile = NULL,
  omnipath = TRUE,
  ligreextra = TRUE,
  kinaseextra = !high_confidence,
  pathwayextra = !high_confidence,
  ...
)
```

Arguments

interactions_param a list with arguments for an interactions query: [import_omnipath_interactions](#), [import_pathwayextra_interactions](#), [import_kinaseextra_interactions](#), [import_ligreextra_interactions](#)

transmitter_param a list with arguments for [import_omnipath_intercell](#), to define the transmitter side of intercellular connections

receiver_param a list with arguments for [import_omnipath_intercell](#), to define the receiver side of intercellular connections

resources A character vector of resources to be applied to both the interactions and the annotations. For example, `resources = 'CellChatDB'` will download the transmitters and receivers defined by CellChatDB, connected by connections from CellChatDB.

entity_types Character, possible values are "protein", "complex" or both.

ligand_receptor Logical. If TRUE, only *ligand* and *receptor* annotations will be used instead of the more generic *transmitter* and *receiver* categories.

high_confidence Logical: shortcut to do some filtering in order to include only higher confidence interactions. The intercell database of OmniPath covers a very broad range of possible ways of cell to cell communication, and the pieces of information, such as localization, topology, function and interaction, are combined from many, often independent sources. This unavoidably result some weird and unexpected combinations which are false positives in the context of intercellular communication. This option sets some minimum criteria to remove most (but definitely not all!) of the wrong connections. These criteria are the followings: 1) the receiver must be plasma membrane transmembrane; 2) the curation effort for interactions must be larger than one; 3) the consensus score for annotations

must be larger than the 50 percentile within the generic category (you can override this by `consensus_percentile`). 4) the transmitter must be secreted or exposed on the plasma membrane. 5) The major localizations have to be supported by at least 30 percent of the relevant resources (you can override this by `loc_consensus_percentile`). 6) The datasets with lower level of curation (*kinaseextra* and *pathwayextra*) will be disabled. These criteria are of medium stringency, you can always tune them to be more relaxed or stringent by filtering manually, using `filter_intercell_network`.

<code>simplify</code>	Logical: keep only the most often used columns. This function combines a network data frame with two copies of the intercell annotation data frames, all of them already having quite some columns. With this option we keep only the names of the interacting pair, their intercellular communication roles, and the minimal information of the origin of both the interaction and the annotations.
<code>unique_pairs</code>	Logical: instead of having separate rows for each pair of annotations, drop the annotations and reduce the data frame to unique interacting pairs. See <code>unique_intercell_network</code> for details.
<code>consensus_percentile</code>	Numeric: a percentile cut off for the consensus score of generic categories in intercell annotations. The consensus score is the number of resources supporting the classification of an entity into a category based on combined information of many resources. Here you can apply a cut-off, keeping only the annotations supported by a higher number of resources than a certain percentile of each category. If NULL no filtering will be performed. The value is either in the 0-1 range, or will be divided by 100 if greater than 1. The percentiles will be calculated against the generic composite categories and then will be applied to their resource specific annotations and specific child categories.
<code>loc_consensus_percentile</code>	Numeric: similar to <code>consensus_percentile</code> for major localizations. For example, with a value of 50, the secreted, plasma membrane transmembrane or peripheral attributes will be TRUE only where at least 50 percent of the resources support these.
<code>omnipath</code>	Logical: shortcut to include the <i>omnipath</i> dataset in the interactions query.
<code>ligreextra</code>	Logical: shortcut to include the <i>ligreextra</i> dataset in the interactions query.
<code>kinaseextra</code>	Logical: shortcut to include the <i>kinaseextra</i> dataset in the interactions query.
<code>pathwayextra</code>	Logical: shortcut to include the <i>pathwayextra</i> dataset in the interactions query.
<code>...</code>	If <code>simplify</code> or <code>unique_pairs</code> is TRUE, additional column names can be passed here to <code>dplyr::select</code> on the final data frame. Otherwise ignored.

Details

By default this function creates almost the largest possible network of intercellular interactions. However, this might contain a large number of false positives. Please refer to the documentation of the arguments, especially `high_confidence`, and the `filter_intercell_network` function. Note: if you restrict the query to certain intercell annotation resources or small categories, it's not recommended to use the `consensus_percentile` or `high_confidence` options, instead filter the network with `filter_intercell_network` for more consistent results.

Value

A dataframe containing information about protein-protein interactions and the inter-cellular roles of the proteins involved in those interactions.

See Also

- [get_intercell_categories](#)
- [get_intercell_generic_categories](#)
- [import_omnipath_intercell](#)
- [import_omnipath_interactions](#)
- [import_pathwayextra_interactions](#)
- [import_kinaseextra_interactions](#)
- [import_ligrecextra_interactions](#)
- [unique_intercell_network](#)
- [simplify_intercell_network](#)
- [filter_intercell_network](#)

Examples

```
intercell_network <- import_intercell_network(  
  interactions_param = list(datasets = 'ligrecextra'),  
  receiver_param = list(categories = c('receptor', 'transporter')),  
  transmitter_param = list(categories = c('ligand', 'secreted_enzyme'))  
)
```

```
import_kinaseextra_interactions
```

Imports interactions from the 'kinase extra' dataset of OmniPath

Description

Imports the dataset from: <https://omnipathdb.org/interactions?datasets=kinaseextra>, which contains enzyme-substrate interactions without literature reference. The enzyme-substrate interactions supported by literature references are part of the 'omnipath' dataset.

Usage

```
import_kinaseextra_interactions(  
  resources = NULL,  
  organism = 9606,  
  fields = NULL,  
  default_fields = TRUE,  
  references_by_resource = TRUE,  
  exclude = NULL,  
  ...  
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	Optional additional arguments.

Value

A dataframe containing enzyme-substrate interactions without literature reference

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-  
  import_kinaseextra_interactions(  
    resources = c('PhosphoPoint', 'PhosphoSite'),  
    organism = 9606  
  )
```

```
import_ligrecextra_interactions
```

Imports interactions from the 'ligrec extra' dataset of OmniPath

Description

Imports the dataset from: <https://omnipathdb.org/interactions?datasets=ligrecextra>, which contains ligand-receptor interactions without literature reference. The ligand-receptor interactions supported by literature references are part of the 'omnipath' dataset.

Usage

```
import_ligrecextra_interactions(
  resources = NULL,
  organism = 9606,
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	optional additional arguments

Value

A dataframe containing ligand-receptor interactions including the ones without literature references

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <- import_ligrecextra_interactions(
  resources = c('HPRD', 'Guide2Pharma'),
  organism = 9606
)
```

```
import_lncrna_mrna_interactions
```

Imports interactions from the lncRNA-mRNA dataset of OmniPath

Description

Imports the dataset from: https://omnipathdb.org/interactions?datasets=lncrna_mrna, which contains lncRNA-mRNA interactions

Usage

```
import_lncrna_mrna_interactions(
  resources = NULL,
  organism = 9606,
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	optional additional arguments

Value

A dataframe containing lncRNA-mRNA interactions

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_lncrna_mrna_interactions(
    resources = c('ncRDeathDB')
  )
```

```
import_mirnatarget_interactions
```

Imports interactions from the miRNA-target dataset of OmniPath

Description

Imports the dataset from: <https://omnipathdb.org/interactions?datasets=mirnatarget>, which contains miRNA-mRNA interactions.

Usage

```
import_mirnatarget_interactions(
  resources = NULL,
  organism = 9606,
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	optional additional arguments

Value

A dataframe containing miRNA-mRNA interactions

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_mirnatarget_interactions(
    resources = c('miRTarBase', 'miRecords')
  )
```

```
import_omnipath_annotations
      Imports annotations from OmniPath
```

Description

Imports protein annotations about function, localization, expression, structure and other properties of proteins from OmniPath <https://omnipathdb.org/annotations>. Note: there might be also a few miRNAs annotated; a vast majority of protein complex annotations are inferred from the annotations of the members: if all members carry the same annotation the complex inherits.

Usage

```
import_omnipath_annotations(
  proteins = NULL,
  resources = NULL,
  wide = FALSE,
  ...
)
```

Arguments

proteins	Vector containing the genes or proteins for whom annotations will be retrieved (UniProt IDs or HGNC Gene Symbols or miRBase IDs). It is also possible to download annotations for protein complexes. To do so, write 'COMPLEX:' right before the genesymbols of the genes integrating the complex. Check the vignette for examples.
resources	Load the annotations only from these databases. See get_annotation_resources for possible values.
wide	Convert the annotation table to wide format, which corresponds more or less to the original resource. If the data comes from more than one resource a list of wide tables will be returned. See examples at pivot_annotations .
...	Additional arguments.

Details

Downloading the full annotations dataset is disabled by default because the size of this data is around 1GB. We recommend to retrieve the annotations for a set of proteins or only from a few resources, depending on your interest. You can always download the full database from https://archive.omnipathdb.org/omnipath_webservice_annotations__recent.tsv using any standard R or readr method.

Value

A data frame containing different gene and complex annotations.

See Also

- [get_annotation_databases](#)
- [pivot_annotations](#)

Examples

```
annotations <- import_omnipath_annotations(  
  proteins = c('TP53', 'LMNA'),  
  resources = c('HPA_subcellular')  
)
```

```
import_omnipath_complexes
```

Imports protein complexes from OmniPath

Description

Imports the complexes stored in Omnipath database from <https://omnipathdb.org/complexes>.

Usage

```
import_omnipath_complexes(resources = NULL, ...)
```

Arguments

resources	complexes not reported in these databases are removed. See get_complexes_databases for more information.
...	optional additional arguments

Value

A dataframe containing information about complexes

See Also

- [get_complexes_databases](#)

Examples

```
complexes = import_omnipath_complexes(
    resources = c('CORUM', 'hu.MAP')
)
```

```
import_omnipath_enzsub
```

Imports enzyme-substrate relationships from OmniPath

Description

Imports the enzyme-substrate (more exactly, enzyme-PTM) relationship database from <https://omnipathdb.org/enzsub>

Usage

```
import_omnipath_enzsub(
  resources = NULL,
  organism = 9606,
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	PTMs not reported in these databases are removed. See get_ptms_databases for more information.
organism	PTMs are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	You can define here additional fields to be added to the result. If used, set the next argument, <code>default_fields</code> , to FALSE.
default_fields	Whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the <code>fields</code> argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	Optional additional arguments.

Value

A data frame containing the information about ptms

See Also

- [get_enzsub_resources](#)
- [import_omnipath_interactions](#)
- [enzsub_graph](#)
- [print_interactions](#)

Examples

```
enzsub <- import_omnipath_enzsub(
  resources = c('PhosphoSite', 'SIGNOR'),
  organism = 9606
)
```

```
import_omnipath_interactions
```

Imports interactions from the 'omnipath' dataset of Omnipath

Description

Imports the database from <https://omnipathdb.org/interactions>, which contains only interactions supported by literature references. This part of the interaction database compiled a similar way as it has been presented in the first paper describing OmniPath (Turei et al. 2016).

Usage

```
import_omnipath_interactions(
  resources = NULL,
  organism = 9606,
  datasets = "omnipath",
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
datasets	Names of the interaction datasets to download: omnipath (by default). Other possibilities are: pathwayextra, kinaseextra, ligreextra, dorothea,tf_target, mirnatarget, tf_mirna, lncrna_mrna. The user can select multiple datasets as for example: c('omnipath', 'pathwayextra', 'kinaseextra')
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.

default_fields whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.

references_by_resource if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.

exclude Character: datasets or resources to exclude.

... optional additional arguments

Value

A dataframe of protein-protein interactions

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions = import_omnipath_interactions(
  resources = c('Signalink3'),
  organism = 9606
)
```

```
import_omnipath_intercell
```

Imports OmniPath intercell annotations

Description

Imports the OmniPath intercellular communication role annotation database from <https://omnipathdb.org/intercell>. It provides information on the roles in inter-cellular signaling. E.g. if a protein is a ligand, a receptor, an extracellular matrix (ECM) component, etc.

Usage

```
import_omnipath_intercell(
  categories = NULL,
  resources = NULL,
  parent = NULL,
  scope = NULL,
  aspect = NULL,
  source = NULL,
  transmitter = NULL,
  receiver = NULL,
  secreted = NULL,
```

```

plasma_membrane_peripheral = NULL,
plasma_membrane_transmembrane = NULL,
proteins = NULL,
topology = NULL,
causality = NULL,
consensus_percentile = NULL,
loc_consensus_percentile = NULL,
...
)

```

Arguments

categories	vector containing the categories to be retrieved. All the genes belonging to those categories will be returned. For further information about the categories see codeget_intercell_categories .
resources	limit the query to certain resources; see the available resources by get_intercell_resources .
parent	vector containing the parent classes to be retrieved. All the genes belonging to those classes will be returned. For further information about the main classes see get_intercell_categories .
scope	either 'specific' or 'generic'
aspect	either 'locational' or 'functional'
source	either 'resource_specific' or 'composite'
transmitter	logical, include only transmitters i.e. proteins delivering signal from a cell to its environment.
receiver	logical, include only receivers i.e. proteins delivering signal to the cell from its environment.
secreted	logical, include only secreted proteins
plasma_membrane_peripheral	logical, include only plasma membrane peripheral membrane proteins.
plasma_membrane_transmembrane	logical, include only plasma membrane transmembrane proteins.
proteins	limit the query to certain proteins
topology	topology categories: one or more of 'secreted' (sec), 'plasma_membrane_peripheral' (pmp), 'plasma_membrane_transmembrane' (pmtm) (both short or long notation can be used).
causality	'transmitter' (trans), 'receiver' (rec) or 'both' (both short or long notation can be used).
consensus_percentile	Numeric: a percentile cut off for the consensus score of generic categories. The consensus score is the number of resources supporting the classification of an entity into a category based on combined information of many resources. Here you can apply a cut-off, keeping only the annotations supported by a higher number of resources than a certain percentile of each category. If NULL no filtering will be performed. The value is either in the 0-1 range, or will be divided by 100 if greater than 1. The percentiles will be calculated against the generic composite categories and then will be applied to their resource specific annotations and specific child categories.

loc_consensus_percentile
Numeric: similar to codeconsensus_percentile for major localizations. For example, with a value of 50, the secreted, plasma membrane transmembrane or peripheral attributes will be true only where at least 50 percent of the resources support these.

... Additional optional arguments, ignored.

Value

A dataframe containing information about roles in intercellular signaling.

See Also

- [get_intercell_categories](#)
- [get_intercell_generic_categories](#)
- [import_intercell_network](#)
- [intercell_consensus_filter](#)

Examples

```
intercell <- import_omnipath_intercell(categories = 'ecm')
```

```
import_pathwayextra_interactions
```

Imports interactions from the 'pathway extra' dataset of Omnipath

Description

Imports the dataset from: <https://omnipathdb.org/interactions?datasets=pathwayextra>, which contains activity flow interactions without literature reference. The activity flow interactions supported by literature references are part of the 'omnipath' dataset.

Usage

```
import_pathwayextra_interactions(  
  resources = NULL,  
  organism = 9606,  
  fields = NULL,  
  default_fields = TRUE,  
  references_by_resource = TRUE,  
  exclude = NULL,  
  ...  
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose one of those: 9606 human (default), 10116 rat or 10090 Mouse.
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	optional additional arguments

Value

A dataframe containing activity flow interactions between proteins without literature reference

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_pathwayextra_interactions(
    resources = c('BioGRID', 'IntAct'),
    organism = 9606
  )
```

```
import_post_translational_interactions
  Imports all post-translational interactions from OmniPath
```

Description

Imports the dataset from all post-translational datasets of OmniPath.

Usage

```
import_post_translational_interactions(
  resources = NULL,
  organism = 9606,
  exclude = NULL,
  references_by_resource = TRUE,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
exclude	Character: datasets or resources to exclude.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
...	optional additional arguments

Value

A dataframe containing post-translational interactions

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_post_translational_interactions(
    resources = c('BioGRID')
  )
```

```
import_tf_mirna_interactions
```

Imports interactions from the TF-miRNA dataset of OmniPath

Description

Imports the dataset from: https://omnipathdb.org/interactions?datasets=tf_mirna, which contains transcription factor-miRNA gene interactions

Usage

```
import_tf_mirna_interactions(
  resources = NULL,
  organism = 9606,
  fields = NULL,
  default_fields = TRUE,
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	optional additional arguments

Value

A dataframe containing TF-miRNA interactions

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_tf_mirna_interactions(
    resources = c('TransmiR')
  )
```

```
import_tf_target_interactions
```

Imports interactions from the TF-target dataset of OmniPath

Description

Imports the dataset from: https://omnipathdb.org/interactions?datasets=tf_target, which contains transcription factor-target protein coding gene interactions. Note: this is not the only TF-target dataset in OmniPath, 'dorothea' is the other one and the 'tf_mirna' dataset provides TF-miRNA gene interactions.

Usage

```
import_tf_target_interactions(
    resources = NULL,
    organism = 9606,
    fields = NULL,
    default_fields = TRUE,
    references_by_resource = TRUE,
    exclude = NULL,
    ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
fields	The user can define here the fields to be added. If used, set the next argument, 'default_fields', to FALSE.
default_fields	whether to include the default fields (columns) for the query type. If FALSE, only the fields defined by the user in the 'fields' argument will be added.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	Optional additional arguments

Value

A dataframe containing TF-target interactions

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_tf_target_interactions(
    resources = c('DoRothEA', 'SIGNOR')
  )
```

```
import_transcriptional_interactions
  Imports all TF-target interactions from OmniPath
```

Description

Imports the dataset from: https://omnipathdb.org/interactions?datasets=tf_target,dorothea, which contains transcription factor-target protein coding gene interactions.

Usage

```
import_transcriptional_interactions(
  resources = NULL,
  organism = 9606,
  dorothea_levels = c("A", "B"),
  references_by_resource = TRUE,
  exclude = NULL,
  ...
)
```

Arguments

resources	interactions not reported in these databases are removed. See get_interaction_resources for more information.
organism	Interactions are available for human, mouse and rat. Choose among: 9606 human (default), 10116 rat and 10090 Mouse
dorothea_levels	Vector detailing the confidence levels of the interactions to be downloaded. In dorothea, every TF-target interaction has a confidence score ranging from A to E, being A the most reliable interactions. By default we take A and B level interactions (c(A,B)). It is to note that E interactions are not available in OmnipathR.
references_by_resource	if FALSE, removes the resource name prefixes from the references (PubMed IDs); this way the information which reference comes from which resource will be lost and the PubMed IDs will be unique.
exclude	Character: datasets or resources to exclude.
...	Optional additional arguments.

Value

A dataframe containing TF-target interactions.

See Also

- [get_interaction_resources](#)
- [import_all_interactions](#)
- [interaction_graph](#)
- [print_interactions](#)

Examples

```
interactions <-
  import_transcriptional_interactions(
    resources = c('PAZAR', 'ORegAnno', 'DoRothEA')
  )
```

inbiomap_download	<i>Downloads and preprocesses network data from InWeb InBioMap</i>
-------------------	--

Description

Downloads the data by [inbiomap_raw](#), extracts the UniProt IDs, Gene Symbols and scores and removes the irrelevant columns.

Usage

```
inbiomap_download(...)
```

Arguments

... Passed to [inbiomap_raw](#).

Value

A data frame (tibble) of interactions.

See Also

[inbiomap_raw](#)

Examples

```
inbiomap_interactions <- inbiomap_download()
inbiomap_interactions

# # A tibble: 625,641 x 7
#   uniprot_a uniprot_b genesymbol_a genesymbol_b inferred score1 score2
#   <chr>     <chr>     <chr>         <chr>         <lgl>   <dbl> <dbl>
# 1 A0A5B9    P01892    TRBC2         HLA-A         FALSE   0.417 0.458
# 2 A0AUZ9    Q96CV9    KANSL1L       OPTN           FALSE   0.155 0.0761
# 3 A0AV02    P24941    SLC12A8       CDK2           TRUE    0.156 0.0783
# 4 A0AV02    Q00526    SLC12A8       CDK3           TRUE    0.157 0.0821
# 5 A0AV96    P0CG48    RBM47         UBC            FALSE   0.144 0.0494
# # . with 625,631 more rows
```

inbiomap_raw	<i>Downloads network data from InWeb InBioMap</i>
--------------	---

Description

Downloads the data from <https://inbio-discover.com/map.html#downloads> in tar.gz format, extracts the PSI MITAB table and returns it as a data frame.

Usage

```
inbiomap_raw(curl_verbose = FALSE)
```

Arguments

`curl_verbose` Logical. Perform CURL requests in verbose mode for debugging purposes.

Value

A data frame (tibble) with the extracted interaction table.

See Also

[inbiomap_download](#)

Examples

```
inbiomap_psimitab <- inbiomap_raw()
```

interaction_graph	<i>Build Omnipath interaction graph</i>
-------------------	---

Description

Transforms the interactions data frame to an igraph graph object.

Usage

```
interaction_graph(interactions = interactions)
```

Arguments

`interactions` data.frame created by

- [import_omnipath_enzsub](#)
- [import_omnipath_interactions](#)
- [import_pathwayextra_interactions](#)
- [import_kinaseextra_interactions](#)
- [import_ligreextra_interactions](#)
- [import_post_translational_interactions](#)

- [import_dorothea_interactions](#)
- [import_tf_target_interactions](#)
- [import_transcriptional_interactions](#)
- [import_mirnatarget_interactions](#)
- [import_all_interactions](#)

Value

An igraph graph object.

See Also

- [import_omnipath_interactions](#)
- [import_pathwayextra_interactions](#)
- [import_kinaseextra_interactions](#)
- [import_ligreextra_interactions](#)
- [import_dorothea_interactions](#)
- [import_mirnatarget_interactions](#)
- [import_all_interactions](#)
- [giant_component](#)
- [find_all_paths](#)

Examples

```
interactions <- import_omnipath_interactions(resources = c('Signalink3'))
g <- interaction_graph(interactions)
```

`intercell_categories` *Full list of intercell categories and resources*

Description

Full list of intercell categories and resources

Usage

```
intercell_categories()
```

Value

A data frame of categories and resources.

Examples

```
ic_cat <- intercell_categories()
ic_cat
# # A tibble: 1,125 x 3
#   category          parent          database
#   <chr>             <chr>         <chr>
# 1 transmembrane    transmembrane UniProt_location
# 2 transmembrane    transmembrane UniProt_topology
# 3 transmembrane    transmembrane UniProt_keyword
# 4 transmembrane    transmembrane_predicted Phobius
# 5 transmembrane_phobius transmembrane_predicted Almen2009
# # . with 1,120 more rows
```

```
intercell_consensus_filter
```

Quality filter for intercell annotations

Description

Quality filter for intercell annotations

Usage

```
intercell_consensus_filter(data, percentile = NULL, loc_percentile = NULL)
```

Arguments

data	A data frame with intercell annotations, as provided by import_omnipath_intercell .
percentile	Numeric: a percentile cut off for the consensus score of composite categories. The consensus score is the number of resources supporting the classification of an entity into a category based on combined information of many resources. Here you can apply a cut-off, keeping only the annotations supported by a higher number of resources than a certain percentile of each category. If NULL no filtering will be performed. The value is either in the 0-1 range, or will be divided by 100 if greater than 1. The percentiles will be calculated against the generic composite categories and then will be applied to their resource specific annotations and specific child categories.
loc_percentile	Numeric: similar to percentile for major localizations. For example, with a value of 50, the secreted, plasma membrane transmembrane or peripheral attributes will be TRUE only where at least 50 percent of the resources support these.

Value

The data frame in data filtered by the consensus scores.

Examples

```
intercell <- import_omnipath_intercell(parent = c('ligand', 'receptor'))
nrow(intercell)
# [1] 50174
intercell_q50 <- intercell_consensus_filter(intercell, 50)
nrow(intercell_q50)
# [1] 42863
```

is_ontology_id	<i>Looks like an ontology ID</i>
----------------	----------------------------------

Description

Tells if the input has the typical format of ontology IDs, i.e. a code of capital letters, a colon, followed by a numeric code.

Usage

```
is_ontology_id(terms)
```

Arguments

terms Character vector with strings to check.

Value

A logical vector with the same length as the input.

Examples

```
is_ontology_id(c('GO:0000001', 'reproduction'))
# [1] TRUE FALSE
```

kegg_info	<i>Information about a KEGG Pathway</i>
-----------	---

Description

Information about a KEGG Pathway

Usage

```
kegg_info(pathway_id)
```

Arguments

pathway_id Character: a KEGG Pathway identifier, e.g. "hsa04710". For a complete list of IDs see [kegg_pathway_list](#).

Value

List with the pathway information.

See Also

- [kegg_pathway_list](#)
- [kegg_picture](#)
- [kegg_open](#)

Examples

```
kegg_info('map00563')
```

kegg_open

Open a KEGG Pathway diagram in the browser

Description

Open a KEGG Pathway diagram in the browser

Usage

```
kegg_open(pathway_id)
```

Arguments

pathway_id Character: a KEGG Pathway identifier, e.g. "hsa04710". For a complete list of IDs see [kegg_pathway_list](#).

Details

To open URLs in the web browser the "browser" option must be set to a a valid executable. You can check the value of this option by `getOption("browser")`. If your browser is firefox and the executable is located in the system path, you can set the option to point to it: `options(browser = "firefox")`. To make it a permanent setting, you can also include this in your `.Rprofile` file.

Value

Returns NULL.

See Also

- [kegg_pathway_list](#)
- [kegg_picture](#)
- [kegg_info](#)

Examples

```
if(any(getOption('browser') != '')) kegg_open('hsa04710')
```

`kegg_pathways_download`*Download the KEGG Pathways database*

Description

Downloads all pathway diagrams in the KEGG Pathways database in KGML format and processes the XML to extract the interactions.

Usage

```
kegg_pathways_download(max_expansion = NULL, simplify = FALSE)
```

Arguments

`max_expansion` Numeric: the maximum number of relations derived from a single relation record. As one entry might represent more than one molecular entities, one relation might yield a large number of relations in the processing. This happens in a combinatorial way, e.g. if the two entries represent 3 and 4 entities, that results 12 relations. If NULL, all relations will be expanded.

`simplify` Logical: remove KEGG's internal identifiers and the pathway annotations, keep only unique interactions with direction and effect sign.

Value

A data frame (tibble) of interactions.

See Also

- [kegg_pathway_list](#)
- [kegg_process](#)
- [kegg_pathway_download](#)

Examples

```
kegg_pw <- kegg_pathways_download(simplify = TRUE)
kegg_pw
# # A tibble: 6,765 x 6
#   uniprot_source uniprot_target type effect genesymbol_source
#   <chr>          <chr>          <chr> <chr> <chr>
# 1 Q03113         Q15283         PPre1 activ. GNA12
# 2 Q9Y4G8         P62070         PPre1 activ. RAPGEF2
# 3 Q13972         P62070         PPre1 activ. RASGRF1
# 4 O95267         P62070         PPre1 activ. RASGRP1
# 5 P62834         P15056         PPre1 activ. RAP1A
# # . with 6,760 more rows, and 1 more variable: genesymbol_target <chr>
```

kegg_pathway_download *Download one KEGG pathway*

Description

Downloads one pathway diagram from the KEGG Pathways database in KGML format and processes the XML to extract the interactions.

Usage

```
kegg_pathway_download(
  pathway_id,
  process = TRUE,
  max_expansion = NULL,
  simplify = FALSE
)
```

Arguments

pathway_id	Character: a KEGG pathway identifier, for example "hsa04350".
process	Logical: process the data or return it in raw format. processing means joining the entries and relations into a single data frame and adding UniProt IDs.
max_expansion	Numeric: the maximum number of relations derived from a single relation record. As one entry might represent more than one molecular entities, one relation might yield a large number of relations in the processing. This happens in a combinatorial way, e.g. if the two entries represent 3 and 4 entities, that results 12 relations. If NULL, all relations will be expanded.
simplify	Logical: remove KEGG's internal identifiers and the pathway annotations, keep only unique interactions with direction and effect sign.

Value

A data frame (tibble) of interactions if process is TRUE, otherwise a list with two data frames: "entries" is a raw table of the entries while "relations" is a table of relations extracted from the KGML file.

See Also

- [kegg_process](#)
- [kegg_pathways_download](#)
- [kegg_pathway_list](#)

Examples

```
tgf_pathway <- kegg_pathway_download('hsa04350')
tgf_pathway
## # A tibble: 50 x 12
##   source target type effect arrow relation_id kegg_id_source
##   <chr> <chr> <chr> <chr> <chr> <chr> <chr>
## 1 51 49 PPre1 activ. --> hsa04350:1 hsa:7040 hsa:.
## 2 57 55 PPre1 activ. --> hsa04350:2 hsa:151449 hs.
```

```
# 3 34    32    PPre1 activ. --> hsa04350:3 hsa:3624 hsa:.
# 4 20    17    PPre1 activ. --> hsa04350:4 hsa:4838
# 5 60    46    PPre1 activ. --> hsa04350:5 hsa:4086 hsa:.
# # . with 45 more rows, and 5 more variables: genesymbol_source <chr>,
# #   uniprot_source <chr>, kegg_id_target <chr>,
# #   genesymbol_target <chr>, uniprot_target <chr>
```

kegg_pathway_list *List of KEGG pathways*

Description

Retrieves a list of available KEGG pathways.

Usage

```
kegg_pathway_list()
```

Value

Data frame of pathway names and identifiers.

See Also

- [kegg_process](#)
- [kegg_pathway_download](#)
- [kegg_pathways_download](#)
- [kegg_open](#)
- [kegg_picture](#)
- [kegg_info](#)

Examples

```
kegg_pws <- kegg_pathway_list()
kegg_pws
# # A tibble: 521 x 2
#   id      name
#   <chr>  <chr>
# 1 map01100 Metabolic pathways
# 2 map01110 Biosynthesis of secondary metabolites
# 3 map01120 Microbial metabolism in diverse environments
# 4 map01200 Carbon metabolism
# 5 map01210 2-Oxocarboxylic acid metabolism
# 6 map01212 Fatty acid metabolism
# 7 map01230 Biosynthesis of amino acids
# # . with 514 more rows
```

kegg_picture	<i>Download a pathway diagram as a picture</i>
--------------	--

Description

Downloads a KEGG Pathway diagram as a PNG image.

Usage

```
kegg_picture(pathway_id, path = NULL)
```

Arguments

pathway_id	Character: a KEGG Pathway identifier, e.g. "hsa04710". For a complete list of IDs see kegg_pathway_list .
path	Character: save the image to this path. If NULL, the image will be saved in the current directory under the name <pathway_id>.png.

Value

Invisibly returns the path to the downloaded file.

See Also

[kegg_pathway_list](#)

- [kegg_pathway_list](#)
- [kegg_open](#)
- [kegg_info](#)

Examples

```
kegg_picture('hsa04710')  
kegg_picture('hsa04710', path = 'foo/bar')  
kegg_picture('hsa04710', path = 'foo/bar/circadian.png')
```

kegg_process	<i>Interactions from KGML</i>
--------------	-------------------------------

Description

Processes KEGG Pathways data extracted from a KGML file. Joins the entries and relations into a single data frame and translates the Gene Symbols to UniProt IDs.

Usage

```
kegg_process(entries, relations, max_expansion = NULL, simplify = FALSE)
```

Arguments

entries	A data frames with entries extracted from a KGML file by kegg_pathway_download .
relations	A data frames with relations extracted from a KGML file by kegg_pathway_download .
max_expansion	Numeric: the maximum number of relations derived from a single relation record. As one entry might represent more than one molecular entities, one relation might yield a large number of relations in the processing. This happens in a combinatorial way, e.g. if the two entries represent 3 and 4 entities, that results 12 relations. If NULL, all relations will be expanded.
simplify	Logical: remove KEGG's internal identifiers and the pathway annotations, keep only unique interactions with direction and effect sign.

Value

A data frame (tibble) of interactions. In rare cases when a pathway doesn't contain any relation, returns NULL.

See Also

- [kegg_pathway_download](#)
- [kegg_pathways_download](#)
- [kegg_pathway_list](#)

Examples

```
hsa04350 <- kegg_pathway_download('hsa04350', process = FALSE)
tgf_pathway <- kegg_process(hsa04350$entries, hsa04350$relations)
tgf_pathway
# # A tibble: 50 x 12
#   source target type effect arrow relation_id kegg_id_source
#   <chr> <chr> <chr> <chr> <chr> <chr> <chr>
# 1 51 49 PPre1 activ. --> hsa04350:1 hsa:7040 hsa:.
# 2 57 55 PPre1 activ. --> hsa04350:2 hsa:151449 hs.
# 3 34 32 PPre1 activ. --> hsa04350:3 hsa:3624 hsa:.
# 4 20 17 PPre1 activ. --> hsa04350:4 hsa:4838
# 5 60 46 PPre1 activ. --> hsa04350:5 hsa:4086 hsa:.
# # . with 45 more rows, and 5 more variables: genesymbol_source <chr>,
# # uniprot_source <chr>, kegg_id_target <chr>,
# # genesymbol_target <chr>, uniprot_target <chr>
```

load_db

Load a built in database

Description

Load a built in database

Usage

```
load_db(key, param = list())
```

Arguments

key	Character: the key of the database to load. For a list of available keys see omnipath_show_db .
param	List: override the defaults or pass further parameters to the database loader function. See the loader functions and their default parameters in omnipath_show_db .

Details

This function loads a database which is stored within the package namespace until its expiry. The loaded database is accessible by [get_db](#) and the loading process is typically initiated by [get_db](#), not by the users directly.

Value

Returns NULL.

See Also

[omnipath_show_db](#).

Examples

```
load_db('go_slim')
omnipath_show_db()
```

nichenet_build_model *Construct a NicheNet ligand-target model*

Description

Construct a NicheNet ligand-target model

Usage

```
nichenet_build_model(optimization_results, networks, use_weights = TRUE)
```

Arguments

optimization_results	The outcome of NicheNet parameter optimization as produced by nichenet_optimization .
networks	A list with NicheNet format signaling, ligand-receptor and gene regulatory networks as produced by nichenet_networks .
use_weights	Logical: whether to use the optimized weights.

Value

A named list with two elements: 'weighted_networks' and 'optimized_parameters'.

Examples

```
expression <- nichenet_expression_data()

networks <- nichenet_networks()
optimization_results <- nichenet_optimization(networks, expression)
nichenet_model <- nichenet_build_model(optimization_results, networks)
```

nichenet_expression_data

Expression data from ligand-receptor perturbation experiments used by NicheNet

Description

NicheNet uses expression data from a collection of published ligand or receptor KO or perturbation experiments to build its model. This function retrieves the original expression data, deposited in Zenodo (<https://zenodo.org/record/3260758>).

Usage

```
nichenet_expression_data()
```

Value

Nested list, each element contains a data frame of processed expression data and key variables about the experiment.

Examples

```
exp_data <- nichenet_expression_data()
head(names(exp_data))
# [1] "bmp4_tgfb"      "tgfb_bmp4"      "nodal_Nodal"    "spectrum_IL4"
# [5] "spectrum_Tnf"  "spectrum_Ifng"
purrr::map_chr(head(exp_data), 'from')
#   bmp4_tgfb    tgfb_bmp4    nodal_Nodal  spectrum_IL4  spectrum_Tnf
#   "BMP4"       "TGFB1"       "NODAL"      "IL4"         "TNF"
# spectrum_Ifng
#   "IFNG"
```

nichenet_gr_network *Builds a NicheNet gene regulatory network*

Description

Builds gene regulatory network prior knowledge for NicheNet using multiple resources.

Usage

```
nichenet_gr_network(  
  omnipath = list(),  
  harmonizome = list(),  
  regnetwork = list(),  
  htridb = list(),  
  remap = list(),  
  evex = list(),  
  pathwaycommons = list(),  
  trrust = list(),  
  only_omnipath = FALSE  
)
```

Arguments

omnipath	List with paramaters to be passed to nichenet_gr_network_omnipath .
harmonizome	List with paramaters to be passed to nichenet_gr_network_harmonizome .
regnetwork	List with paramaters to be passed to nichenet_gr_network_regnetwork .
htridb	List with paramaters to be passed to nichenet_gr_network_htridb .
remap	List with paramaters to be passed to nichenet_gr_network_remap .
evex	List with paramaters to be passed to nichenet_gr_network_evex .
pathwaycommons	List with paramaters to be passed to nichenet_gr_network_pathwaycommons .
trrust	List with paramaters to be passed to nichenet_gr_network_trrust .
only_omnipath	Logical: a shortcut to use only OmniPath as network resource.

Value

A network data frame (tibble) with gene regulatory interactions suitable for use with NicheNet.

See Also

- [nichenet_gr_network_evex](#)
- [nichenet_gr_network_harmonizome](#)
- [nichenet_gr_network_htridb](#)
- [nichenet_gr_network_omnipath](#)
- [nichenet_gr_network_pathwaycommons](#)
- [nichenet_gr_network_regnetwork](#)
- [nichenet_gr_network_remap](#)
- [nichenet_gr_network_trrust](#)

Examples

```
# load everything with the default parameters:
gr_network <- nichenet_gr_network()

# less targets from ReMap, not using RegNetwork:
gr_network <- nichenet_gr_network(
  # I needed to disable ReMap here due to some issues
  # of one of the Bioconductor build servers
  # remap = list(top_targets = 200),
  remap = NULL,
  regnetwork = NULL,
)

# use only OmniPath:
gr_network_omnipath <- nichenet_gr_network(only_omnipath = TRUE)
```

nichenet_gr_network_evex

NicheNet gene regulatory network from EVEX

Description

Builds a gene regulatory network using data from the EVEX database and converts it to a format suitable for NicheNet.

Usage

```
nichenet_gr_network_evex(
  top_confidence = 0.75,
  indirect = FALSE,
  regulation_of_expression = FALSE
)
```

Arguments

top_confidence Double, between 0 and 1. Threshold based on the quantile of the confidence score.

indirect Logical: whether to include indirect interactions.

regulation_of_expression Logical: whether to include also the "regulation of expression" type interactions.

Value

Data frame of interactions in NicheNet format.

Data frame with gene regulatory interactions in NicheNet format.

See Also

- [nichenet_gr_network](#)
- [evex_download](#)

Examples

```
# use only the 10% with the highest confidence:
evex_gr_network <- nichenet_gr_network_evex(top_confidence = .9)
```

```
nichenet_gr_network_harmonizome
```

NicheNet gene regulatory network from Harmonizome

Description

Builds gene regulatory network prior knowledge for NicheNet using Harmonizome

Usage

```
nichenet_gr_network_harmonizome(  
  datasets = c("cheappi", "encodetfppi", "jasparpwm", "transfac", "transfacpwm",  
              "motifmap", "geotf", "geokinase", "geogene"),  
  ...  
)
```

Arguments

datasets	The datasets to use. For possible values please refer to default value and the Harmonizome webpage.
...	Ignored.

Value

Data frame with gene regulatory interactions in NicheNet format.

See Also

- [nichenet_gr_network](#)
- [harmonizome_download](#)

Examples

```
# use only JASPAR and TRANSFAC:
hz_gr_network <- nichenet_gr_network_harmonizome(  
  datasets = c('jasparpwm', 'transfac', 'transfacpwm')  
)
```

`nichenet_gr_network_htridb`*NicheNet gene regulatory network from HTRIdb*

Description

Builds a gene regulatory network using data from the HTRIdb database and converts it to a format suitable for NicheNet.

Usage

```
nichenet_gr_network_htridb()
```

Value

Data frame with gene regulatory interactions in NicheNet format.

See Also

[htridb_download](#), [nichenet_gr_network](#)

Examples

```
htri_gr_network <- nichenet_gr_network_htridb()
```

`nichenet_gr_network_omnipath`*Builds gene regulatory network for NicheNet using OmniPath*

Description

Retrieves network prior knowledge from OmniPath and provides it in a format suitable for NicheNet. This method never downloads the 'ligreextra' dataset because the ligand-receptor interactions are supposed to come from [nichenet_lr_network_omnipath](#).

Usage

```
nichenet_gr_network_omnipath(min_curation_effort = 0, ...)
```

Arguments

`min_curation_effort`

Lower threshold for curation effort

`...`

Passed to [import_transcriptional_interactions](#)

Value

A network data frame (tibble) with gene regulatory interactions suitable for use with NicheNet.

See Also

- [nichenet_gr_network_evex](#)
- [nichenet_gr_network_harmonizome](#)
- [nichenet_gr_network_htridb](#)
- [nichenet_gr_network_omnipath](#)
- [nichenet_gr_network_pathwaycommons](#)
- [nichenet_gr_network_regnetwork](#)
- [nichenet_gr_network_remap](#)
- [nichenet_gr_network_trrust](#)

Examples

```
# use interactions up to confidence level "C" from DoRothEA:
op_gr_network <- nichenet_gr_network_omnipath(
  dorothea_levels = c('A', 'B', 'C')
)
```

```
nichenet_gr_network_pathwaycommons
```

NicheNet gene regulatory network from PathwayCommons

Description

Builds gene regulation prior knowledge for NicheNet using PathwayCommons.

Usage

```
nichenet_gr_network_pathwaycommons(
  interaction_types = "controls-expression-of",
  ...
)
```

Arguments

```
interaction_types
```

Character vector with PathwayCommons interaction types. Please refer to the default value and the PathwayCommons webpage.

```
...
```

Ignored.

Value

Data frame with gene regulatory interactions in NicheNet format.

See Also

- [nichenet_gr_network](#)
- [pathwaycommons_download](#)

Examples

```
pc_gr_network <- nichenet_gr_network_pathwaycommons()
```

```
nichenet_gr_network_regnetwork
```

NicheNet gene regulatory network from RegNetwork

Description

Builds a gene regulatory network using data from the RegNetwork database and converts it to a format suitable for NicheNet.

Usage

```
nichenet_gr_network_regnetwork()
```

Value

Data frame with gene regulatory interactions in NicheNet format.

See Also

- [regnetwork_download](#)
- [nichenet_gr_network](#)

Examples

```
regn_gr_network <- nichenet_gr_network_regnetwork()
```

```
nichenet_gr_network_remap
```

NicheNet gene regulatory network from ReMap

Description

Builds a gene regulatory network using data from the ReMap database and converts it to a format suitable for NicheNet.

Usage

```
nichenet_gr_network_remap(  
  score = 100,  
  top_targets = 500,  
  only_known_tfs = TRUE  
)
```

Arguments

- score Numeric: a minimum score between 0 and 1000, records with lower scores will be excluded. If NULL no filtering performed.
- top_targets Numeric: the number of top scoring targets for each TF. Essentially the maximum number of targets per TF. If NULL the number of targets is not restricted.
- only_known_tfs Logical: whether to exclude TFs which are not in TF census.

Value

Data frame with gene regulatory interactions in NicheNet format.

See Also

- [remap_filtered](#)
- [nichenet_gr_network](#)

Examples

```
# use only max. top 100 targets for each TF:
remap_gr_network <- nichenet_gr_network_remap(top_targets = 100)
```

nichenet_gr_network_trrust

NicheNet gene regulatory network from TRRUST

Description

Builds a gene regulatory network using data from the TRRUST database and converts it to a format suitable for NicheNet.

Usage

```
nichenet_gr_network_trrust()
```

Value

Data frame with gene regulatory interactions in NicheNet format.

See Also

- [trrust_download](#)
- [nichenet_gr_network](#)

Examples

```
trrust_gr_network <- nichenet_gr_network_trrust()
```

nichenet_ligand_activities

Calls the NicheNet ligand activity analysis

Description

Calls the NicheNet ligand activity analysis

Usage

```
nichenet_ligand_activities(
  ligand_target_matrix,
  lr_network,
  expressed_genes_transmitter,
  expressed_genes_receiver,
  genes_of_interest,
  background_genes = NULL,
  n_top_ligands = 42,
  n_top_targets = 250
)
```

Arguments

ligand_target_matrix

A matrix with rows and columns corresponding to ligands and targets, respectively. Produced by [nichenet_ligand_target_matrix](#) or `nichenetr::construct_ligand_target`.

lr_network

A data frame with ligand-receptor interactions, as produced by [nichenet_lr_network](#).

expressed_genes_transmitter

Character vector with the gene symbols of the genes expressed in the cells transmitting the signal.

expressed_genes_receiver

Character vector with the gene symbols of the genes expressed in the cells receiving the signal.

genes_of_interest

Character vector with the gene symbols of the genes of interest. These are the genes in the receiver cell population that are potentially affected by ligands expressed by interacting cells (e.g. genes differentially expressed upon cell-cell interaction).

background_genes

Character vector with the gene symbols of the genes to be used as background.

n_top_ligands

How many of the top ligands to include in the ligand-target table.

n_top_targets

For each ligand, how many of the top targets to include in the ligand-target table.

Value

A named list with 'ligand_activities' (a tibble giving several ligand activity scores; following columns in the tibble: \$test_ligand, \$auc, \$aupr and \$pearson) and 'ligand_target_links' (a tibble with columns ligand, target and weight (i.e. regulatory potential score)).

Examples

```

networks <- nichenet_networks()
expression <- nichenet_expression_data()
optimization_results <- nichenet_optimization(networks, expression)
nichenet_model <- nichenet_build_model(optimization_results, networks)
lt_matrix <- nichenet_ligand_target_matrix(
  nichenet_model$weighted_networks,
  networks$lr_network,
  nichenet_model$optimized_parameters
)
ligand_activities <- nichenet_ligand_activities(
  ligand_target_matrix = lt_matrix,
  lr_network = networks$lr_network,
  # the rest of the parameters should come
  # from your transcriptomics data:
  expressed_genes_transmitter = expressed_genes_transmitter,
  expressed_genes_receiver = expressed_genes_receiver,
  genes_of_interest = genes_of_interest
)

```

nichenet_ligand_target_links

Compiles a table with weighted ligand-target links

Description

A wrapper around `nichenetr::get_weighted_ligand_target_links` to compile a data frame with weighted links from the top ligands to their top targets.

Usage

```

nichenet_ligand_target_links(
  ligand_activities,
  ligand_target_matrix,
  genes_of_interest,
  n_top_ligands = 42,
  n_top_targets = 250
)

```

Arguments

`ligand_activities`

Ligand activity table as produced by `nichenetr::predict_ligand_activities`.

`ligand_target_matrix`

Ligand-target matrix as produced by `nichenetr::construct_ligand_target_matrix` or the wrapper around it in the current package: [nichenet_ligand_target_matrix](#).

`genes_of_interest`

Character vector with the gene symbols of the genes of interest. These are the genes in the receiver cell population that are potentially affected by ligands expressed by interacting cells (e.g. genes differentially expressed upon cell-cell interaction).

`n_top_ligands` How many of the top ligands to include in the ligand-target table.
`n_top_targets` For each ligand, how many of the top targets to include in the ligand-target table.

Value

A tibble with columns `ligand`, `target` and `weight` (i.e. regulatory potential score).

Examples

```
networks <- nichenet_networks()
expression <- nichenet_expression_data()
optimization_results <- nichenet_optimization(networks, expression)
nichenet_model <- nichenet_build_model(optimization_results, networks)
lt_matrix <- nichenet_ligand_target_matrix(
  nichenet_model$weighted_networks,
  networks$lr_network,
  nichenet_model$optimized_parameters
)
ligand_activities <- nichenet_ligand_activities(
  ligand_target_matrix = lt_matrix,
  lr_network = networks$lr_network,
  # the rest of the parameters should come
  # from your transcriptomics data:
  expressed_genes_transmitter = expressed_genes_transmitter,
  expressed_genes_receiver = expressed_genes_receiver,
  genes_of_interest = genes_of_interest
)
lt_links <- nichenet_ligand_target_links(
  ligand_activities = ligand_activities,
  ligand_target_matrix = lt_matrix,
  genes_of_interest = genes_of_interest,
  n_top_ligands = 20,
  n_top_targets = 100
)
```

`nichenet_ligand_target_matrix`

Creates a NicheNet ligand-target matrix

Description

Creates a NicheNet ligand-target matrix

Usage

```
nichenet_ligand_target_matrix(
  weighted_networks,
  lr_network,
  optimized_parameters,
  use_weights = TRUE,
  construct_ligand_target_matrix_param = list()
)
```

Arguments

- `weighted_networks` Weighted networks as provided by `nichenet_build_model`.
- `lr_network` A data frame with ligand-receptor interactions, as produced by `nichenet_lr_network`.
- `optimized_parameters` The outcome of NicheNet parameter optimization as produced by `nichenet_build_model`.
- `use_weights` Logical: whether the network sources are weighted. In this function it only affects the output file name.
- `construct_ligand_target_matrix_param` Override parameters for `nichenetr::construct_ligand_target_matrix`.

Value

A matrix containing ligand-target probability scores.

Examples

```
networks <- nichenet_networks()
expression <- nichenet_expression_data()
optimization_results <- nichenet_optimization(networks, expression)
nichenet_model <- nichenet_build_model(optimization_results, networks)
lt_matrix <- nichenet_ligand_target_matrix(
  nichenet_model$weighted_networks,
  networks$lr_network,
  nichenet_model$optimized_parameters
)
```

`nichenet_lr_network` *Builds a NicheNet ligand-receptor network*

Description

Builds ligand-receptor network prior knowledge for NicheNet using multiple resources.

Usage

```
nichenet_lr_network(
  omnipath = list(),
  guide2pharma = list(),
  ramilowski = list(),
  only_omnipath = FALSE,
  quality_filter_param = list()
)
```

Arguments

omnipath	List with parameters to be passed to nichenet_lr_network_omnipath .
guide2pharma	List with parameters to be passed to nichenet_lr_network_guide2pharma .
ramilowski	List with parameters to be passed to nichenet_lr_network_ramilowski .
only_omnipath	Logical: a shortcut to use only OmniPath as network resource.
quality_filter_param	Arguments for filter_intercell_network (quality filtering of the OmniPath ligand-receptor network). It is recommended to check these parameters and apply some quality filtering. The defaults already ensure certain filtering, but you might want more relaxed or stringent options.

Value

A network data frame (tibble) with ligand-receptor interactions suitable for use with NicheNet.

See Also

- [nichenet_lr_network_omnipath](#)
- [nichenet_lr_network_guide2pharma](#)
- [nichenet_lr_network_ramilowski](#)
- [filter_intercell_network](#)

Examples

```
# load everything with the default parameters:
lr_network <- nichenet_lr_network()

# don't use Ramilowski:
lr_network <- nichenet_lr_network(ramilowski = NULL)

# use only OmniPath:
lr_network_omnipath <- nichenet_lr_network(only_omnipath = TRUE)
```

nichenet_lr_network_guide2pharma

Ligand-receptor network from Guide to Pharmacology

Description

Downloads ligand-receptor interactions from the Guide to Pharmacology database and converts it to a format suitable for NicheNet.

Usage

```
nichenet_lr_network_guide2pharma()
```

Value

Data frame with ligand-receptor interactions in NicheNet format.

See Also

[nichenet_lr_network](#), [guide2pharma_download](#)

Examples

```
g2p_lr_network <- nichenet_lr_network_guide2pharma()
```

nichenet_lr_network_omnipath

Builds ligand-receptor network for NicheNet using OmniPath

Description

Retrieves network prior knowledge from OmniPath and provides it in a format suitable for NicheNet. This method never downloads the 'ligreextra' dataset because the ligand-receptor interactions are supposed to come from [nichenet_lr_network_omnipath](#).

Usage

```
nichenet_lr_network_omnipath(quality_filter_param = list(), ...)
```

Arguments

quality_filter_param

List with arguments for [filter_intercell_network](#). It is recommended to check these parameters and apply some quality filtering. The defaults already ensure certain filtering, but you might want more relaxed or stringent options.

...

Passed to [import_intercell_network](#)

Value

A network data frame (tibble) with ligand-receptor interactions suitable for use with NicheNet.

See Also

- [nichenet_lr_network](#)
- [import_intercell_network](#)

Examples

```
# use only ligand-receptor interactions (not for example ECM-adhesion):
op_lr_network <- nichenet_lr_network_omnipath(ligand_receptor = TRUE)

# use only CellPhoneDB and Guide to Pharmacology:
op_lr_network <- nichenet_lr_network_omnipath(
  resources = c('CellPhoneDB', 'Guide2Pharma')
)

# only interactions where the receiver is a transporter:
op_lr_network <- nichenet_lr_network_omnipath(
  receiver_param = list(parent = 'transporter')
)
```

`nichenet_lr_network_ramilowski`*Ligand-receptor network from Ramilowski 2015*

Description

Downloads ligand-receptor interactions from Supplementary Table 2 of the paper 'A draft network of ligand-receptor-mediated multicellular signalling in human' (Ramilowski et al. 2015, <https://www.nature.com/articles/ncomms8866>). It converts the downloaded table to a format suitable for NicheNet.

Usage

```
nichenet_lr_network_ramilowski(  
  evidences = c("literature supported", "putative")  
)
```

Arguments

`evidences` Character: evidence types, "literature supported", "putative" or both.

Value

Data frame with ligand-receptor interactions in NicheNet format.

See Also

- [nichenet_lr_network](#)
- [ramilowski_download](#)

Examples

```
# use only the literature supported data:  
rami_lr_network <- nichenet_lr_network_ramilowski(  
  evidences = 'literature supported'  
)
```

`nichenet_main`*Executes the full NicheNet pipeline*

Description

Builds all prior knowledge data required by NicheNet. For this it calls a multitude of methods to download and combine data from various databases according to the settings. The content of the prior knowledge data is highly customizable, see the documentation of the related functions. After the prior knowledge is ready, it performs parameter optimization to build a NicheNet model. This results a weighted ligand- target matrix. Then, considering the expressed genes from user provided data, a gene set of interest and background genes, it executes the NicheNet ligand activity analysis.

Usage

```
nichenet_main(
  only_omnipath = FALSE,
  expressed_genes_transmitter = NULL,
  expressed_genes_receiver = NULL,
  genes_of_interest = NULL,
  background_genes = NULL,
  use_weights = TRUE,
  n_top_ligands = 42,
  n_top_targets = 250,
  signaling_network = list(),
  lr_network = list(),
  gr_network = list(),
  small = FALSE,
  tiny = FALSE,
  make_multi_objective_function_param = list(),
  objective_function_param = list(),
  mlrmo_optimization_param = list(),
  construct_ligand_target_matrix_param = list(),
  results_dir = NULL,
  quality_filter_param = list()
)
```

Arguments

- only_omnipath** Logical: use only OmniPath for network knowledge. This is a simple switch for convenience, further options are available by the other arguments. By default we use all available resources. The networks can be customized on a resource by resource basis, as well as providing custom parameters for individual resources, using the parameters 'signaling_network', 'lr_network' and 'gr_network'.
- expressed_genes_transmitter** Character vector with the gene symbols of the genes expressed in the cells transmitting the signal.
- expressed_genes_receiver** Character vector with the gene symbols of the genes expressed in the cells receiving the signal.
- genes_of_interest** Character vector with the gene symbols of the genes of interest. These are the genes in the receiver cell population that are potentially affected by ligands expressed by interacting cells (e.g. genes differentially expressed upon cell-cell interaction).
- background_genes** Character vector with the gene symbols of the genes to be used as background.
- use_weights** Logical: calculate and use optimized weights for resources (i.e. one resource seems to be better than another, hence the former is considered with a higher weight).
- n_top_ligands** How many of the top ligands to include in the ligand-target table.
- n_top_targets** How many of the top targets (for each of the top ligands) to consider in the ligand-target table.
- signaling_network** A list of parameters for building the signaling network, passed to [nichenet_signaling_network](#).

lr_network	A list of parameters for building the ligand-receptor network, passed to nichenet_lr_network .
gr_network	A list of parameters for building the gene regulatory network, passed to nichenet_gr_network .
small	Logical: build a small network for testing purposes, using only OmniPath data. It is also a high quality network, it is reasonable to try the analysis with this small network.
tiny	Logical: build an even smaller network for testing purposes. As this involves random subsetting, it's not recommended to use this network for analysis.
make_multi_objective_function_param	Override parameters for <code>smoof::makeMultiObjectiveFunction</code> .
objective_function_param	Override additional arguments passed to the objective function.
mlrmo_optimization_param	Override arguments for <code>nichenetr::mlrmo_optimization</code> .
construct_ligand_target_matrix_param	Override parameters for <code>nichenetr::construct_ligand_target_matrix</code> .
results_dir	Character: path to the directory to save intermediate and final outputs from NicheNet methods.
quality_filter_param	Arguments for filter_intercell_network (quality filtering of the OmniPath ligand-receptor network). It is recommended to check these parameters and apply some quality filtering. The defaults already ensure certain filtering, but you might want more relaxed or stringent options.

Details

About *small* and *tiny* networks: Building a NicheNet model is computationally demanding, taking several hours to run. As this is related to the enormous size of the networks, to speed up testing we can use smaller networks, around 1,000 times smaller, with few thousands of interactions instead of few millions. Random subsetting of the whole network would result disjunct fragments, instead we load only a few resources. To run the whole pipeline with tiny networks use [nichenet_test](#).

Value

A named list with the intermediate and final outputs of the pipeline: 'networks', 'expression', 'optimized_parameters', 'weighted_networks' and 'ligand_target_matrix'.

See Also

- [nichenet_networks](#)
- [nichenet_signaling_network](#)
- [nichenet_lr_network](#)
- [nichenet_gr_network](#)
- [nichenet_test](#)
- [nichenet_workarounds](#)
- [nichenet_results_dir](#)

Examples

```
nichenet_results <- nichenet_main(
  # altering some network resource parameters, the rest
  # of the resources will be loaded according to the defaults
  signaling_network = list(
    cpdb = NULL, # this resource will be excluded
    inbiomap = NULL,
    evex = list(min_confidence = 1.0) # override some parameters
  ),
  gr_network = list(only_omnipath = TRUE),
  n_top_ligands = 20,
  # override the default number of CPU cores to use
  mlrmo_optimization_param = list(ncores = 4)
)
```

nichenet_networks *Builds NicheNet network prior knowledge*

Description

Builds network knowledge required by NicheNet. For this it calls a multitude of methods to download and combine data from various databases according to the settings. The content of the prior knowledge data is highly customizable, see the documentation of the related functions.

Usage

```
nichenet_networks(
  signaling_network = list(),
  lr_network = list(),
  gr_network = list(),
  only_omnipath = FALSE,
  small = FALSE,
  tiny = FALSE,
  quality_filter_param = list()
)
```

Arguments

signaling_network	A list of parameters for building the signaling network, passed to nichenet_signaling_network
lr_network	A list of parameters for building the ligand-receptor network, passed to nichenet_lr_network
gr_network	A list of parameters for building the gene regulatory network, passed to nichenet_gr_network
only_omnipath	Logical: a shortcut to use only OmniPath as network resource.
small	Logical: build a small network for testing purposes, using only OmniPath data. It is also a high quality network, it is reasonable to try the analysis with this small network.
tiny	Logical: build an even smaller network for testing purposes. As this involves random subsetting, it's not recommended to use this network for analysis.

quality_filter_param

Arguments for `filter_intercell_network` (quality filtering of the OmniPath ligand-receptor network). It is recommended to check these parameters and apply some quality filtering. The defaults already ensure certain filtering, but you might want more relaxed or stringent options.

Value

A named list with three network data frames (tibbles): the signaling, the ligand-receptor (lr) and the gene regulatory (gr) networks.

See Also

- [nichenet_signaling_network](#)
- [nichenet_lr_network](#)
- [nichenet_gr_network](#)

Examples

```
networks <- nichenet_networks()
dplyr::sample_n(networks$gr_network, 10)
# # A tibble: 10 x 4
#   from   to     source      database
#   <chr> <chr> <chr>      <chr>
# 1 MAX   ALG3   harmonizome_ENCODE harmonizome
# 2 MAX   IMPDH1 harmonizome_ENCODE harmonizome
# 3 SMAD5 LCP1   Remap_5     Remap
# 4 HNF4A TNFRSF19 harmonizome_CHEA harmonizome
# 5 SMC3   FAP    harmonizome_ENCODE harmonizome
# 6 E2F6   HIST1H1B harmonizome_ENCODE harmonizome
# 7 TFAP2C MAT2B   harmonizome_ENCODE harmonizome
# 8 USF1   TBX4   harmonizome_TRANSFAC harmonizome
# 9 MIR133B FETUB   harmonizome_TRANSFAC harmonizome
# 10 SP4    HNRNP2 harmonizome_ENCODE harmonizome

# use only OmniPath:
omnipath_networks <- nichenet_networks(only_omnipath = TRUE)
```

nichenet_optimization *Optimizes NicheNet model parameters*

Description

Optimize NicheNet method parameters, i.e. PageRank parameters and source weights, based on a collection of experiments where the effect of a ligand on gene expression was measured.

Usage

```
nichenet_optimization(
  networks,
  expression,
  make_multi_objective_function_param = list(),
  objective_function_param = list(),
  mlrmo_optimization_param = list()
)
```

Arguments

networks A list with NicheNet format signaling, ligand-receptor and gene regulatory networks as produced by [nichenet_networks](#).

expression A list with expression data from ligand perturbation experiments, as produced by [nichenet_expression_data](#).

make_multi_objective_function_param Override parameters for `smoof::makeMultiObjectiveFunction`.

objective_function_param Override additional arguments passed to the objective function.

mlrmo_optimization_param Override arguments for `nichenetr::mlrmo_optimization`.

Value

A result object from the function 'mlrMBO::mbo'. Among other things, this contains the optimal parameter settings, the output corresponding to every input etc.

Examples

```
networks <- nichenet_networks()
expression <- nichenet_expression_data()
optimization_results <- nichenet_optimization(networks, expression)
```

nichenet_remove_orphan_ligands

Removes experiments with orphan ligands

Description

Removes from the expression data the perturbation experiments involving ligands without connections.

Usage

```
nichenet_remove_orphan_ligands(expression, lr_network)
```

Arguments

expression Expression data as returned by [nichenet_expression_data](#).

lr_network A NicheNet format ligand-receptor network data frame as produced by [nichenet_lr_network](#).

Value

The same list as 'expression' with certain elements removed.

Examples

```
lr_network <- nichenet_lr_network()
expression <- nichenet_expression_data()
expression <- nichenet_remove_orphan_ligands(expression, lr_network)
```

nichenet_results_dir *Path to the current NicheNet results directory*

Description

Path to the directory to save intermediate and final outputs from NicheNet methods.

Usage

```
nichenet_results_dir()
```

Value

Character: path to the NicheNet results directory.

Examples

```
nichenet_results_dir()
# [1] "nichenet_results"
```

nichenet_signaling_network
Builds a NicheNet signaling network

Description

Builds signaling network prior knowledge for NicheNet using multiple resources.

Usage

```
nichenet_signaling_network(
  omnipath = list(),
  pathwaycommons = list(),
  harmonizome = list(),
  vinayagam = list(),
  cpdb = list(),
  evex = list(),
  inbiomap = list(),
  only_omnipath = FALSE
)
```

Arguments

omnipath	List with parameters to be passed to nichenet_signaling_network_omnipath .
pathwaycommons	List with parameters to be passed to nichenet_signaling_network_pathwaycommons .
harmonizome	List with parameters to be passed to nichenet_signaling_network_harmonizome .
vinayagam	List with parameters to be passed to nichenet_signaling_network_vinayagam .
cpdb	List with parameters to be passed to nichenet_signaling_network_cpdb .
evex	List with parameters to be passed to nichenet_signaling_network_evex .
inbiomap	List with parameters to be passed to nichenet_signaling_network_inbiomap .
only_omnipath	Logical: a shortcut to use only OmniPath as network resource.

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

See Also

- [nichenet_signaling_network_omnipath](#)
- [nichenet_signaling_network_pathwaycommons](#)
- [nichenet_signaling_network_harmonizome](#)
- [nichenet_signaling_network_vinayagam](#)
- [nichenet_signaling_network_cpdb](#)
- [nichenet_signaling_network_evex](#)
- [nichenet_signaling_network_inbiomap](#)

Examples

```
# load everything with the default parameters:
# we don't load inBio Map due to the - hopefully
# temporary - issues of their server
sig_network <- nichenet_signaling_network(inbiomap = NULL)

# override parameters for some resources:
sig_network <- nichenet_signaling_network(
  omnipath = list(resources = c('SIGNOR', 'Signalink3', 'SPIKE')),
  pathwaycommons = NULL,
  harmonizome = list(datasets = c('phosphositeplus', 'depod')),
  cpdb = list(complex_max_size = 1, min_score = .98),
  evex = list(min_confidence = 1.5),
  inbiomap = NULL
)

# use only OmniPath:
sig_network_omnipath <- nichenet_signaling_network(only_omnipath = TRUE)
```

`nichenet_signaling_network_cpdb`*Builds signaling network for NicheNet using ConsensusPathDB*

Description

Builds signaling network prior knowledge using ConsensusPathDB (CPDB) data. Note, the interactions from CPDB are not directed and many of them comes from complex expansion. Find out more at <http://cpdb.molgen.mpg.de/>.

Usage

```
nichenet_signaling_network_cpdb(...)
```

Arguments

... Passed to [consensuspathdb_download](#).

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

See Also

- [nichenet_signaling_network](#)
- [consensuspathdb_download](#)

Examples

```
# use some parameters stricter than default:
cpdb_signaling_network <- nichenet_signaling_network_cpdb(
  complex_max_size = 2,
  min_score = .99
)
```

`nichenet_signaling_network_evex`*NicheNet signaling network from EVEX*

Description

Builds signaling network prior knowledge for NicheNet from the EVEX database.

Usage

```
nichenet_signaling_network_evex(top_confidence = 0.75, indirect = FALSE, ...)
```

Arguments

top_confidence	Double, between 0 and 1. Threshold based on the quantile of the confidence score.
indirect	Logical: whether to include indirect interactions.
...	Ignored.

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

See Also

- [evex_download](#)
- [nichenet_signaling_network](#)

Examples

```
ev_signaling_network <- nichenet_signaling_network_evex(  
  top_confidence = .9  
)
```

nichenet_signaling_network_harmonizome
NicheNet signaling network from Harmonizome

Description

Builds signaling network prior knowledge for NicheNet using Harmonizome

Usage

```
nichenet_signaling_network_harmonizome(  
  datasets = c("phosphositeplus", "kea", "depod"),  
  ...  
)
```

Arguments

datasets	The datasets to use. For possible values please refer to default value and the Harmonizome webpage.
...	Ignored.

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

Examples

```
# use only KEA and PhosphoSite:
hz_signaling_network <- nichenet_signaling_network_harmonizome(
  datasets = c('kea', 'phosphositeplus')
)
```

```
nichenet_signaling_network_inbiomap
NicheNet signaling network from InWeb InBioMap
```

Description

Builds signaling network prior knowledge for NicheNet from the InWeb InBioMap database.

Usage

```
nichenet_signaling_network_inbiomap(...)
```

Arguments

```
... Ignored.
```

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

See Also

[nichenet_signaling_network](#), [inbiomap_download](#)

Examples

```
ib_signaling_network <- nichenet_signaling_network_inbiomap()
```

```
nichenet_signaling_network_omnipath
Builds signaling network for NicheNet using OmniPath
```

Description

Retrieves network prior knowledge from OmniPath and provides it in a format suitable for NicheNet. This method never downloads the 'ligreextra' dataset because the ligand-receptor interactions are supposed to come from [nichenet_lr_network_omnipath](#).

Usage

```
nichenet_signaling_network_omnipath(min_curation_effort = 0, ...)
```

Arguments

min_curation_effort
 Lower threshold for curation effort

...
 Passed to [import_post_translational_interactions](#)

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

See Also

- [nichenet_signaling_network](#)

Examples

```
# use interactions with at least 2 evidences (reference or database)
op_signaling_network <- nichenet_signaling_network_omnipath(
  min_curation_effort = 2
)
```

nichenet_signaling_network_pathwaycommons
NicheNet signaling network from PathwayCommons

Description

Builds signaling network prior knowledge for NicheNet using PathwayCommons.

Usage

```
nichenet_signaling_network_pathwaycommons(
  interaction_types = c("catalysis-precedes", "controls-phosphorylation-of",
    "controls-state-change-of", "controls-transport-of", "in-complex-with",
    "interacts-with"),
  ...
)
```

Arguments

interaction_types
 Character vector with PathwayCommons interaction types. Please refer to the default value and the PathwayCommons webpage.

...
 Ignored.

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

Examples

```
# use only the "controls-transport-of" interactions:
pc_signaling_network <- nichenet_signaling_network_pathwaycommons(
  interaction_types = 'controls-transport-of'
)
```

nichenet_signaling_network_vinayagam
NicheNet signaling network from Vinayagam

Description

Builds signaling network prior knowledge for NicheNet using Vinayagam 2011 Supplementary Table S6. Find out more at <https://doi.org/10.1126/scisignal.2001699>.

Usage

```
nichenet_signaling_network_vinayagam(...)
```

Arguments

... Ignored.

Value

A network data frame (tibble) with signaling interactions suitable for use with NicheNet.

Examples

```
vi_signaling_network <- nichenet_signaling_network_vinayagam()
```

nichenet_test *Run the NicheNet pipeline with a little dummy network*

Description

Loads a tiny network and runs the NicheNet pipeline with low number of iterations in the optimization process. This way the pipeline runs in a reasonable time in order to test the code. Due to the random subsampling disconnected networks might be produced sometimes. If you see an error like "Error in if (sd(prediction_vector) == 0) ... missing value where TRUE/FALSE needed", the random subsampled input is not appropriate. In this case just interrupt and call again. This test ensures the computational integrity of the pipeline. If it fails during the optimization process, try to start it over several times, even restarting R. The unpredictability is related to codemlrMBO and nichenetr not being prepared to handle certain conditions, and it's also difficult to find out which conditions lead to which errors. At least 3 different errors appear time to time, depending on the input. It also seems like restarting R sometimes helps, suggesting that the entire system might be somehow stateful. You can ignore the Parallelization was not stopped warnings on repeated runs.

Usage

```
nichenet_test(...)
```

Arguments

```
...          Passed to nichenet\_main.
```

Value

A named list with the intermediate and final outputs of the pipeline: 'networks', 'expression', 'optimized_parameters', 'weighted_networks' and 'ligand_target_matrix'.

Examples

```
nnt <- nichenet_test()
```

nichenet_workarounds *Workarounds using NicheNet without attaching the package*

Description

NicheNet requires the availability of some lazy loaded external data which are not available if the package is not loaded and attached. Also, the `BBmisc::convertToShortString` used for error reporting in `mlrMBO::evalTargetFun.OptState` is patched here to print longer error messages. Maybe it's a better solution to attach `nichenetr` before running the NicheNet pipeline. Alternatively you can try to call this function in the beginning. Why we don't call this automatically is just because we don't want to load datasets from another package without the user knowing about it.

Usage

```
nichenet_workarounds()
```

Value

Returns NULL.

Examples

```
nichenet_workarounds()
```

`obo_parser`*Generic OBO parser*

Description

Reads the contents of an OBO file and processes it into data frames or a list based data structure.

Usage

```
obo_parser(  
  path,  
  relations = c("is_a", "part_of", "occurs_in", "regulates", "positively_regulates",  
               "negatively_regulates"),  
  shorten_namespace = TRUE,  
  tables = TRUE  
)
```

Arguments

<code>path</code>	Path to the OBO file.
<code>relations</code>	Character vector: process only these relations.
<code>shorten_namespace</code>	Logical: shorten the namespace to a single letter code (as usual for Gene Ontology, e.g. <code>cellular_component = "C"</code>).
<code>tables</code>	Logical: return data frames (tibbles) instead of nested lists.

Value

A list with the following elements: 1) "names" a list with terms as names and names as values; 2) "namespaces" a list with terms as names and namespaces as values; 3) "relations" a list with relations between terms: terms are keys, values are lists with relations as names and character vectors of related terms as values; 4) "subsets" a list with terms as keys and character vectors of subset names as values (or NULL if the term does not belong to any subset); 5) "obsolete" character vector with all the terms labeled as obsolete. If the `tables` parameter is TRUE, "names", "namespaces", "relations" and "subsets" will be data frames (tibbles).

See Also

- [relations_list_to_table](#)
- [relations_table_to_list](#)
- [swap_relations](#)

Examples

```
goslim_url <-  
  "http://current.geneontology.org/ontology/subsets/goslim_generic.obo"  
path <- tempfile()  
httr::GET(goslim_url, httr::write_disk(path, overwrite = TRUE))  
obo <- obo_parser(path, tables = FALSE)  
unlink(path)  
names(obo)
```

```
# [1] "names"      "namespaces" "relations"  "subsets"    "obsolete"
head(obo$relations, n = 2)
# $`GO:0000001`
# $`GO:0000001`$is_a
# [1] "GO:0048308" "GO:0048311"
#
# $`GO:0000002`
# $`GO:0000002`$is_a
# [1] "GO:0007005"
```

OmnipathR

The OmnipathR package

Description

OmnipathR is an R package built to provide easy access to the data stored in the OmniPath web service:

<https://omnipathdb.org/>

And a number of other resources, such as BioPlex, ConsensusPathDB, EVEX, Guide to Pharmacology (IUPHAR/BPS), Harmonizome, HTRIdb, InWeb InBioMap, KEGG Pathway, Pathway Commons, Ramilowski et al. 2015, RegNetwork, ReMap, TF census, TRRUST and Vinayagam et al. 2011.

The OmniPath web service implements a very simple REST style API. This package make requests by the HTTP protocol to retrieve the data. Hence, fast Internet access is required for a proper use of OmnipathR.

The package also provides some utility functions to filter, analyse and visualize the data. Furthermore, OmnipathR features a close integration with the NicheNet method for ligand activity prediction from transcriptomics data, and its R implementation nichenetr (available in CRAN).

Author(s)

Alberto Valdeolivas <<alvaldeolivas@gmail>> and Denes Turei <<turei.denes@gmail.com>> and Attila Gabor <<gaborattila87@gmail.com>>

Examples

```
# Download post-translational modifications:
enzsub <- import_omnipath_enzsub(resources = c("PhosphoSite", "SIGNOR"))

# Download protein-protein interactions
interactions <- import_omnipath_interactions(resources = c("SignalLink3"))

# Convert to igraph objects:
enzsub_g <- enzsub_graph(enzsub = enzsub)
OPI_g <- interaction_graph(interactions = interactions )

# Print some interactions:
print_interactions(head(ptms))

# interactions with references:
print_interactions(tail(ptms),writeRefs=TRUE)
```

```
# find interactions between kinase and substrate:
print_interactions(dplyr::filter(ptms,enzyme_genesymbol=="MAP2K1",
  substrate_genesymbol=="MAPK3"))

# find shortest paths on the directed network between proteins
print_path_es(shortest_paths(OPI_g, from = "TYR03", to = "STAT3",
  output = 'epath')$epath[[1]], OPI_g)

# find all shortest paths between proteins
print_path_vs(
  all_shortest_paths(
    enzsub_g,
    from = "SRC",
    to = "STAT1"
  )$res,
  enzsub_g
)
```

omnipath_cache_autoclean

Keeps only the latest versions of complete downloads

Description

Removes the old versions, the failed downloads and the files in the cache directory which are missing from the database. For more flexible operations use [omnipath_cache_remove](#) and [omnipath_cache_clean](#).

Usage

```
omnipath_cache_autoclean()
```

Value

Invisibl returns the cache database (list of cache records).

Examples

```
omnipath_cache_autoclean()
```

omnipath_cache_clean	<i>Removes the items from the cache directory which are unknown by the cache database</i>
----------------------	---

Description

Removes the items from the cache directory which are unknown by the cache database

Usage

```
omnipath_cache_clean()
```

Value

Returns 'NULL'.

Examples

```
omnipath_cache_clean()
```

omnipath_cache_clean_db	<i>Removes the cache database entries without existing files</i>
-------------------------	--

Description

Removes the cache database entries without existing files

Usage

```
omnipath_cache_clean_db(...)
```

Arguments

... Ignored.

Value

Returns 'NULL'.

Examples

```
omnipath_cache_clean_db()
```

`omnipath_cache_download_ready`*Sets the download status to ready for a cache item*

Description

Sets the download status to ready for a cache item

Usage

```
omnipath_cache_download_ready(version, key = NULL)
```

Arguments

<code>version</code>	Version of the cache item. If does not exist a new version item will be created
<code>key</code>	Key of the cache item

Value

Character: invisibly returns the version number of the cache version item.

Examples

```
bioc_url <- 'https://bioconductor.org/'
# request a new version item (or retrieve the latest)
new_version <- omnipath_cache_latest_or_new(url = bioc_url)
# check if the version item is not a finished download
new_version$status
# [1] "unknown"
# download the file
httr::GET(bioc_url, httr::write_disk(new_version$path, overwrite = TRUE))
# report to the cache database that the download is ready
omnipath_cache_download_ready(new_version)
# now the status is ready:
version <- omnipath_cache_latest_or_new(url = bioc_url)
version$status
# "ready"
version$dl_finished
# [1] "2021-03-09 16:48:38 CET"
omnipath_cache_remove(url = bioc_url) # cleaning up
```

`omnipath_cache_filter_versions`*Filters the versions from one cache record*

Description

Filters the versions based on multiple conditions: their age and status

Usage

```
omnipath_cache_filter_versions(
  record,
  latest = FALSE,
  max_age = NULL,
  min_age = NULL,
  status = CACHE_STATUS$READY
)
```

Arguments

record	A cache record
latest	Return the most recent version
max_age	The maximum age in days (e.g. 5: 5 days old or more recent)
min_age	The minimum age in days (e.g. 5: 5 days old or older)
status	Character vector with status codes. By default only the versions with 'ready' (completed download) status are selected

Value

Character vector with version IDs, NA if no version satisfies the conditions.

Examples

```
# creating an example cache record
bioc_url <- 'https://bioconductor.org/'
version <- omnipath_cache_latest_or_new(url = bioc_url)
httr::GET(bioc_url, httr::write_disk(version$path, overwrite = TRUE))
omnipath_cache_download_ready(version)
record <- dplyr::first(omnipath_cache_search('biocond'))

# only the versions with status "ready"
version_numbers <- omnipath_cache_filter_versions(record, status = 'ready')
omnipath_cache_remove(url = bioc_url) # cleaning up
```

omnipath_cache_get *Retrieves one item from the cache directory*

Description

Retrieves one item from the cache directory

Usage

```
omnipath_cache_get(
  key = NULL,
  url = NULL,
  post = NULL,
  payload = NULL,
  create = TRUE,
  ...
)
```


Arguments

key	The key of the cache record
url	URL pointing to the resource
post	HTTP POST parameters as a list
payload	HTTP data payload
create	Create a new entry if doesn't exist yet
...	Passed to omnipath_cache_record (internal function)

Value

Cache record: an existing record if the entry already exists, otherwise a newly created and inserted record

Examples

```
# create an example cache record
bioc_url <- 'https://bioconductor.org/'
version <- omnipath_cache_latest_or_new(url = bioc_url)
omnipath_cache_remove(url = bioc_url) # cleaning up

# retrieve the cache record
record <- omnipath_cache_get(url = bioc_url)
record$key
# [1] "41346a00fb20d2a9df03aa70cf4d50bf88ab154a"
record$url
# [1] "https://bioconductor.org/"
```

omnipath_cache_key *Generates a hash which identifies an element in the cache database*

Description

Generates a hash which identifies an element in the cache database

Usage

```
omnipath_cache_key(url, post = NULL, payload = NULL)
```

Arguments

url	Character vector with URLs
post	List with the HTTP POST parameters or a list of lists if the url vector is longer than 1. NULL for queries without POST parameters.
payload	HTTP data payload. List with multiple items if the url vector is longer than 1. NULL for queries without data.

Value

Character vector of cache record keys.

Examples

```
bioc_url <- 'https://bioconductor.org/'
omnipath_cache_key(bioc_url)
# [1] "41346a00fb20d2a9df03aa70cf4d50bf88ab154a"
```

omnipath_cache_latest_or_new

The latest or a new version of a cache record

Description

Looks up a record in the cache and returns its latest valid version. If the record doesn't exist or no valid version available, creates a new one.

Usage

```
omnipath_cache_latest_or_new(
  key = NULL,
  url = NULL,
  post = NULL,
  payload = NULL,
  create = TRUE,
  ...
)
```

Arguments

key	The key of the cache record
url	URL pointing to the resource
post	HTTP POST parameters as a list
payload	HTTP data payload
create	Logical: whether to create and return a new version. If FALSE only the latest existing valid version is returned, if available.
...	Passed to omnipath_cache_get

Value

A cache version item.

Examples

```
# retrieve the latest version of the first cache record
# found by the search keyword "bioplex"
latest_bioplex <-
  omnipath_cache_latest_or_new(
    names(omnipath_cache_search('bioplex'))[1]
  )

latest_bioplex$dl_finished
```

```
# [1] "2021-03-09 14:28:50 CET"
latest_bioplex$path
# [1] "/home/denes/.cache/OmnipathR/378e0def2ac97985f629-1.rds"

# create an example cache record
bioc_url <- 'https://bioconductor.org/'
version <- omnipath_cache_latest_or_new(url = bioc_url)
omnipath_cache_remove(url = bioc_url) # cleaning up
```

omnipath_cache_latest_version

Finds the most recent version in a cache record

Description

Finds the most recent version in a cache record

Usage

```
omnipath_cache_latest_version(record)
```

Arguments

record A cache record

Value

Character: the version ID with the most recent download finished time

omnipath_cache_load *Loads an R object from the cache*

Description

Loads the object from RDS format.

Usage

```
omnipath_cache_load(
  key = NULL,
  version = NULL,
  url = NULL,
  post = NULL,
  payload = NULL
)
```

Arguments

key	Key of the cache item
version	Version of the cache item. If does not exist or NULL, the latest version will be retrieved
url	URL of the downloaded resource
post	HTTP POST parameters as a list
payload	HTTP data payload

Value

Object loaded from the cache RDS file.

See Also

[omnipath_cache_save](#)

Examples

```
# works only if you have already this item in the cache
intercell_data <- omnipath_cache_load(url = paste0(
  'https://omnipathdb.org/intercell?resources=Adhesome,Almen2009,',
  'Baccin2019,CSPA,CellChatDB&license=academic'
))
class(intercell_data)
# [1] "data.frame"
nrow(intercell_data)
# [1] 16622
attr(intercell_data, 'origin')
# [1] "cache"

# basic example of saving and loading to and from the cache:
bioc_url <- 'https://bioconductor.org/'
bioc_html <- readChar(url(bioc_url), nchars = 99999)
omnipath_cache_save(bioc_html, url = bioc_url)
bioc_html <- omnipath_cache_load(url = bioc_url)
```

omnipath_cache_move_in

Moves an existing file into the cache

Description

Either the key or the URL (with POST and payload) must be provided.

Usage

```
omnipath_cache_move_in(  
  path,  
  key = NULL,  
  version = NULL,  
  url = NULL,  
  post = NULL,  
  payload = NULL,  
  keep_original = FALSE  
)
```

Arguments

path	Path to the source file
key	Key of the cache item
version	Version of the cache item. If does not exist a new version item will be created
url	URL of the downloaded resource
post	HTTP POST parameters as a list
payload	HTTP data payload
keep_original	Whether to keep or remove the original file

Value

Character: invisibly returns the version number of the cache version item.

See Also

[omnipath_cache_save](#)

Examples

```
omnipath_cache_move_in('some/file.zip', url = 'the_download_address')  
  
# basic example of moving a file to the cache:  
  
bioc_url <- 'https://bioconductor.org/'  
html_file <- tempfile(fileext = '.html')  
httr::GET(bioc_url, httr::write_disk(html_file, overwrite = TRUE))  
omnipath_cache_move_in(path = html_file, url = bioc_url)  
omnipath_cache_remove(url = bioc_url) # cleaning up
```

omnipath_cache_remove *Removes contents from the cache directory*

Description

According to the parameters, it can remove contents older than a certain age, or contents having a more recent version, one specific item, or wipe the entire cache.

Usage

```
omnipath_cache_remove(key = NULL, url = NULL, post = NULL,
  payload = NULL, max_age = NULL, min_age = NULL, status = NULL,
  only_latest = FALSE, wipe = FALSE, autoclean = TRUE)
```

Arguments

key	The key of the cache record
url	URL pointing to the resource
post	HTTP POST parameters as a list
payload	HTTP data payload
max_age	Age of cache items in days. Remove everything that is older than this age
min_age	Age of cache items in days. Remove everything more recent than this age
status	Remove items having any of the states listed here
only_latest	Keep only the latest version
wipe	Logical: if TRUE, removes all files from the cache and the cache database. Same as calling omnipath_cache_wipe .
autoclean	Remove the entries about failed downloads, the files in the cache directory which are missing from the cache database, and the entries without existing files in the cache directory

Value

Invisibly returns the cache database (list of cache records).

See Also

- [omnipath_cache_wipe](#)
- [omnipath_cache_clean](#)
- [omnipath_cache_autoclean](#)

Examples

```
# remove all cache data from the BioPlex database
cache_records <- omnipath_cache_search(
  'bioplex',
  ignore.case = TRUE
)
omnipath_cache_remove(names(cache_records))
```

```

# remove a record by its URL
regnetwork_url <- 'http://www.regnetworkweb.org/download/human.zip'
omnipath_cache_remove(url = regnetwork_url)

# remove all records older than 30 days
omnipath_cache_remove(max_age = 30)

# for each record, remove all versions except the latest
omnipath_cache_remove(only_latest = TRUE)

bioc_url <- 'https://bioconductor.org/'
version <- omnipath_cache_latest_or_new(url = bioc_url)
httr::GET(bioc_url, httr::write_disk(version$path, overwrite = TRUE))
omnipath_cache_download_ready(version)
key <- omnipath_cache_key(bioc_url)
omnipath_cache_remove(key = key)

```

omnipath_cache_save *Saves an R object to the cache*

Description

Exports the object in RDS format, creates new cache record if necessary.

Usage

```

omnipath_cache_save(
  data,
  key = NULL,
  version = NULL,
  url = NULL,
  post = NULL,
  payload = NULL
)

```

Arguments

data	An object
key	Key of the cache item
version	Version of the cache item. If does not exist a new version item will be created
url	URL of the downloaded resource
post	HTTP POST parameters as a list
payload	HTTP data payload

Value

Returns invisibly the data itself.

Invisibly returns the 'data'.

See Also[omnipath_cache_move_in](#)**Examples**

```
mydata <- data.frame(a = c(1, 2, 3), b = c('a', 'b', 'c'))
omnipath_cache_save(mydata, url = 'some_dummy_address')
from_cache <- omnipath_cache_load(url = 'some_dummy_address')
from_cache
#   a b
# 1 1 a
# 2 2 b
# 3 3 c
attr(,"origin")
# [1] "cache"

# basic example of saving and loading to and from the cache:
bioc_url <- 'https://bioconductor.org/'
bioc_html <- readChar(url(bioc_url), nchars = 99999)
omnipath_cache_save(bioc_html, url = bioc_url)
bioc_html <- omnipath_cache_load(url = bioc_url)
```

omnipath_cache_search *Searches for cache items*

Description

Searches the cache records by matching the URL against a string or regexp.

Usage

```
omnipath_cache_search(pattern, ...)
```

Arguments

pattern	String or regular expression.
...	Passed to grep

Value

List of cache records matching the pattern.

Examples

```
# find all cache records from the BioPlex database
bioplex_cache_records <- omnipath_cache_search(
  'bioplex',
  ignore.case = TRUE
)
```

`omnipath_cache_set_ext`*Sets the file extension for a cache record*

Description

Sets the file extension for a cache record

Usage

```
omnipath_cache_set_ext(key, ext)
```

Arguments

<code>key</code>	Character: key for a cache item, alternatively a version entry.
<code>ext</code>	Character: the file extension, e.g. "zip".

Value

Returns 'NULL'.

Examples

```
bioc_url <- 'https://bioconductor.org/'
version <- omnipath_cache_latest_or_new(url = bioc_url)
version$path
# [1] "/home/denes/.cache/OmnipathR/41346a00fb20d2a9df03-1"
httr::GET(bioc_url, httr::write_disk(version$path, overwrite = TRUE))
key <- omnipath_cache_key(url = bioc_url)
omnipath_cache_set_ext(key = key, ext = 'html')
version <- omnipath_cache_latest_or_new(url = bioc_url)
version$path
# [1] "/home/denes/.cache/OmnipathR/41346a00fb20d2a9df03-1.html"
record <- omnipath_cache_get(url = bioc_url)
record$ext
# [1] "html"
omnipath_cache_remove(url = bioc_url) # cleaning up
```

`omnipath_cache_update_status`*Updates the status of an existing cache record*

Description

Updates the status of an existing cache record

Usage

```
omnipath_cache_update_status(key, version, status,
                             dl_finished = NULL)
```

Arguments

key	Key of the cache item
version	Version of the cache item. If does not exist a new version item will be created
status	The updated status value
dl_finished	Timestamp for the time when download was finished, if 'NULL' the value remains unchanged

Value

Character: invisibly returns the version number of the cache version item.

Examples

```
bioc_url <- 'https://bioconductor.org/'
latest_version <- omnipath_cache_latest_or_new(url = bioc_url)
key <- omnipath_cache_key(bioc_url)
omnipath_cache_update_status(
  key = key,
  version = latest_version$number,
  status = 'ready',
  dl_finished = Sys.time()
)
omnipath_cache_remove(url = bioc_url) # cleaning up
```

omnipath_cache_wipe *Permanently removes all the cache contents*

Description

After this operation the cache directory will be completely empty, except an empty cache database file.

Usage

```
omnipath_cache_wipe(...)
```

Arguments

... Ignored.

Value

Returns 'NULL'.

See Also

[omnipath_cache_remove](#)

Examples

```
omnipath_cache_wipe()
# the cache is completely empty:
print(omnipath.env$cache)
# list()
list.files(omnipath_get_cachedir())
# [1] "cache.json"
```

omnipath_get_config_path

Current config file path

Description

Current config file path

Usage

```
omnipath_get_config_path(user = FALSE)
```

Arguments

user	Logical: prioritize the user level config even if a config in the current working directory is available.
------	---

Value

Character: path to the config file.

Examples

```
omnipath_get_config_path()
```

omnipath_load_config *Load the package configuration from a config file*

Description

Load the package configuration from a config file

Usage

```
omnipath_load_config(path = NULL, title = "default", user = FALSE, ...)
```

Arguments

path	Path to the config file.
title	Load the config under this title. One config file might contain multiple configurations, each identified by a title. If the title is not available the first section of the config file will be used.
user	Force to use the user level config even if a config file exists in the current directory. By default, the local config files have priority over the user level config.
...	Passed to <code>yaml::yaml.load_file</code> .

Value

Invisibly returns the config as a list.

Examples

```
# load the config from a custom config file:
omnipath_load_config(path = 'my_custom_omnipath_config.yml')
```

omnipath_log

Browse the current OmnipathR log file

Description

Browse the current OmnipathR log file

Usage

```
omnipath_log()
```

Value

Returns 'NULL'.

See Also

[omnipath_logfile](#)

Examples

```
omnipath_log()
# then you can browse the log file, and exit with `q`
```

omnipath_logfile	<i>Returns the path to the current OmnipathR log file</i>
------------------	---

Description

Returns the path to the current OmnipathR log file

Usage

```
omnipath_logfile()
```

Value

Character: path to the current logfile.

See Also

[omnipath_log](#)

Examples

```
omnipath_logfile()
# [1] "/home/denes/omnipathr/omnipathr-log/omnipathr-20210309-1642.log"
```

omnipath_msg	<i>Dispatch a message to the OmnipathR logger</i>
--------------	---

Description

Any package or script can easily send log messages and establish a logging facility with the fantastic 'logger' package. This function serves the only purpose if you want to inject messages into the logger of OmnipathR. Otherwise we recommend to use the 'logger' package directly.

Usage

```
omnipath_msg(level, ...)
```

Arguments

level	Character, numeric or class loglevel. A log level, if character one of the followings: "fatal", "error", "warn", "success", "info", "trace".
...	Arguments for string formatting, passed sprintf or str_glue.

Value

Returns 'NULL'.

Examples

```
omnipath_msg(  
  level = 'success',  
  'Talking to you in the name of OmnipathR, my favourite number is %d',  
  round(runif(1, 1, 10))  
)
```

omnipath_reset_config *Restores the built-in default values of all config parameters*

Description

Restores the built-in default values of all config parameters

Usage

```
omnipath_reset_config(save = NULL)
```

Arguments

save If a path, the restored config will be also saved to this file. If TRUE, the config will be saved to the current default config path (see [omnipath_get_config_path](#)).

Value

The config as a list.

See Also

[omnipath_load_config](#), [omnipath_save_config](#)

Examples

```
# restore the defaults and write them to the default config file:  
omnipath_reset_config()  
omnipath_save_config()
```

omnipath_save_config *Save the current package configuration*

Description

Save the current package configuration

Usage

```
omnipath_save_config(path = NULL, title = "default", local = FALSE)
```

Arguments

path	Path to the config file. Directories and the file will be created if don't exist.
title	Save the config under this title. One config file might contain multiple configurations, each identified by a title.
local	Save into a config file in the current directory instead of a user level config file. When loading, the config in the current directory has priority over the user level config.

Value

Returns 'NULL'.

Examples

```
# after this, all downloads will default to commercial licenses
# i.e. the resources that allow only academic use will be excluded:
options(omnipath.license = 'commercial')
omnipath_save_config()
```

omnipath_set_cachedir *Change the cache directory*

Description

Change the cache directory

Usage

```
omnipath_set_cachedir(path = NULL)
```

Arguments

path	Character: path to the new cache directory. If don't exist, the directories will be created. If the path is an existing cache directory, the package's cache database for the current session will be loaded from the database in the directory. If NULL, the cache directory will be set to its default path.
------	--

Value

Returns NULL.

Examples

```
tmp_cache <- tempdir()
omnipath_set_cachedir(tmp_cache)
# restore the default cache directory:
omnipath_set_cachedir()
```

omnipath_set_console_loglevel

Sets the log level for the console

Description

Use this method to change during a session which messages you want to be printed on the console. Before loading the package, you can set it also by the config file, with the `omnipath.console_loglevel` key.

Usage

```
omnipath_set_console_loglevel(level)
```

Arguments

`level` Character or class 'loglevel'. The desired log level.

Value

Returns 'NULL'.

See Also

[omnipath_set_logfile_loglevel](#)

Examples

```
omnipath_set_console_loglevel('warn')
# or:
omnipath_set_console_loglevel(logger::WARN)
```

omnipath_set_logfile_loglevel
Sets the log level for the logfile

Description

Use this method to change during a session which messages you want to be written into the logfile. Before loading the package, you can set it also by the config file, with the omnipath.loglevel key.

Usage

```
omnipath_set_logfile_loglevel(level)
```

Arguments

level Character or class 'loglevel'. The desired log level.

Value

Returns 'NULL'.

See Also

[omnipath_set_console_loglevel](#)

Examples

```
omnipath_set_logfile_loglevel('info')  
# or:  
omnipath_set_logfile_loglevel(logger::INFO)
```

omnipath_set_loglevel *Sets the log level for the package logger*

Description

Sets the log level for the package logger

Usage

```
omnipath_set_loglevel(level, target = "logfile")
```

Arguments

level Character or class 'loglevel'. The desired log level.
target Character, either 'logfile' or 'console'

Value

Returns 'NULL'.

Examples

```
omnipath_set_loglevel(logger::FATAL, target = 'console')
```

```
omnipath_show_db      Built in database definitions
```

Description

Databases are resources which might be costly to load but can be used many times by functions which usually automatically load and retrieve them from the database manager. Each database has a lifetime and will be unloaded automatically upon expiry.

Usage

```
omnipath_show_db()
```

Value

A data frame with the built in database definitions.

Examples

```
database_definitions <- omnipath_show_db()
database_definitions
# # A tibble: 14 x 10
#   name      last_used      lifetime package loader loader_p.
#   <chr>    <dtm>          <dbl> <chr> <chr> <list>
# 1 Gene Onto. 2021-04-04 20:19:15    300 Omnipat. go_ontol. <named l.
# 2 Gene Onto. NA                      300 Omnipat. go_ontol. <named l.
# 3 Gene Onto. NA                      300 Omnipat. go_ontol. <named l.
# 4 Gene Onto. NA                      300 Omnipat. go_ontol. <named l.
# 5 Gene Onto. NA                      300 Omnipat. go_ontol. <named l.
# ... (truncated)
# # . with 4 more variables: latest_param <list>, loaded <lgl>, db <list>,
# #   key <chr>
```

```
omnipath_unlock_cache_db
      Removes the lock file from the cache directory
```

Description

A lock file in the cache directory avoids simultaneous write and read. It's supposed to be removed after each read and write operation. This might not happen if the process crashes during such an operation. In this case you can manually call this function.

Usage

```
omnipath_unlock_cache_db()
```

Value

Logical: returns TRUE if the cache was locked and now is unlocked; FALSE if it was not locked.

Examples

```
omnipath_unlock_cache_db()
```

ontology_ensure_id *Only ontology IDs*

Description

Converts a mixture of ontology IDs and names to only IDs. If an element of the input is missing from the chosen ontology it will be dropped. This can happen if the ontology is a subset (slim) version, but also if the input is not a valid ID or name.

Usage

```
ontology_ensure_id(terms, db_key = "go_basic")
```

Arguments

terms Character: ontology IDs or term names.
db_key Character: key to identify the ontology database. For the available keys see [omnipath_show_db](#).

Value

Character vector of ontology IDs.

Examples

```
ontology_ensure_id(c('mitochondrion inheritance', 'GO:0001754'))
# [1] "GO:0000001" "GO:0001754"
```

ontology_ensure_name *Only ontology term names*

Description

Converts a mixture of ontology IDs and names to only names. If an element of the input is missing from the chosen ontology it will be dropped. This can happen if the ontology is a subset (slim) version, but also if the input is not a valid ID or name.

Usage

```
ontology_ensure_name(terms, db_key = "go_basic")
```

Arguments

terms Character: ontology IDs or term names.
 db_key Character: key to identify the ontology database. For the available keys see [omnipath_show_db](#).

Value

Character vector of ontology term names.

Examples

```
ontology_ensure_name(c('reproduction', 'GO:0001754', 'foo bar'))
# [1] "eye photoreceptor cell differentiation" "reproduction"
```

ontology_name_id *Translate between ontology IDs and names*

Description

Makes sure that the output contains only valid IDs or term names. The input can be a mixture of IDs and names. The order of the input won't be preserved in the output.

Usage

```
ontology_name_id(terms, ids = TRUE, db_key = "go_basic")
```

Arguments

terms Character: ontology IDs or term names.
 ids Logical: the output should contain IDs or term names.
 db_key Character: key to identify the ontology database. For the available keys see [omnipath_show_db](#).

Value

Character vector of ontology IDs or term names.

Examples

```
ontology_name_id(c('mitochondrion inheritance', 'reproduction'))
# [1] "GO:0000001" "GO:0000003"
ontology_name_id(c('GO:0000001', 'reproduction'), ids = FALSE)
# [1] "mitochondrion inheritance" "reproduction"
```

`pathwaycommons_download`*Interactions from PathwayCommons*

Description

PathwayCommons (<http://www.pathwaycommons.org/>) provides molecular interactions from a number of databases, in either BioPAX or SIF (simple interaction format). This function retrieves all interactions in SIF format. The data is limited to the interacting pair and the type of the interaction.

Usage

```
pathwaycommons_download()
```

Value

A data frame (tibble) with interactions.

Examples

```
pc_interactions <- pathwaycommons_download()
pc_interactions
# # A tibble: 1,884,849 x 3
#   from type                to
#   <chr> <chr>                 <chr>
# 1 A1BG controls-expression-of A2M
# 2 A1BG interacts-with        ABCC6
# 3 A1BG interacts-with        ACE2
# 4 A1BG interacts-with        ADAM10
# 5 A1BG interacts-with        ADAM17
# # . with 1,884,839 more rows
```

`pivot_annotatations`*Converts annotation tables to a wide format*

Description

Use this method to reconstitute the annotation tables into the format of the original resources. With the 'wide=TRUE' option `import_omnipath_annotatations` applies this function to the downloaded data.

Usage

```
pivot_annotatations(annotatations)
```

Arguments

`annotatations` A data frame of annotations downloaded from the OmniPath web service by `import_omnipath_annotatations`.

Value

A wide format data frame (tibble) if the provided data contains annotations from one resource, otherwise a list of wide format tibbles.

See Also

[import_omnipath_annotations](#)

Examples

```
# single resource: the result is a data frame
disgenet <- import_omnipath_annotations(resources = 'DisGeNet')
disgenet <- pivot_annotations(disgenet)
disgenet
## # A tibble: 119,551 x 10
#   uniprot genesymbol entity_type disease score dsi dpi nof_pmid
#   <chr>   <chr>         <chr>   <chr> <chr> <chr> <chr> <chr>
# 1 P04217 A1BG         protein Schizo. . . 0.3  0.857 0.172 1
# 2 P04217 A1BG         protein Hepato. . . 0.3  0.857 0.172 1
# 3 P01023 A2M         protein alpha-. . . 0.31 0.564 0.724 0
# 4 P01023 A2M         protein Fibros. . . 0.3  0.564 0.724 1
# 5 P01023 A2M         protein Hepato. . . 0.3  0.564 0.724 1
## # . with 119,541 more rows, and 2 more variables: nof_snps <chr>,
## #   source <chr>

# multiple resources: the result is a list
annotations <- import_omnipath_annotations(
  resources = c('DisGeNet', 'SignalLink_function', 'DGIdb', 'kinase.com')
)
annotations <- pivot_annotations(annotations)
names(annotations)
# [1] "DGIdb"           "DisGeNet"        "kinase.com"
# [4] "SignalLink_function"
annotations$kinase.com
## # A tibble: 825 x 6
#   uniprot genesymbol entity_type group family subfamily
#   <chr>   <chr>         <chr>   <chr> <chr> <chr>
# 1 P31749 AKT1         protein AGC Akt NA
# 2 P31751 AKT2         protein AGC Akt NA
# 3 Q9Y243 AKT3         protein AGC Akt NA
# 4 O14578 CIT          protein AGC DMPK CRIK
# 5 Q09013 DMPK         protein AGC DMPK GEK
## # . with 815 more rows
```

print_bma_motif_es *Prints BMA motifs to the screen from a sequence of edges*

Description

The motifs can be copy-pasted into a BMA canvas.

Usage

```
print_bma_motif_es(edge_seq, G, granularity = 2)
```

Arguments

edge_seq An igraph edge sequence.
 G An igraph graph object.
 granularity Numeric: granularity value.

Value

Returns 'NULL'.

Examples

```
interactions <- import_omnipath_interactions(resources = 'ARN')
graph <- interaction_graph(interactions)
print_bma_motif_es(igraph::E(graph)[1], graph)
# {"Model": {
#   "Name": "Omnipath motif",
#   "Variables": [{
#     "Name": "ULK1",
#     "Id": 1,
#     "RangeFrom": 0,
#     "RangeTo": 2,
#     "Formula": ""
#   }],
#   {
#     "Name": "ATG13",
#     ...
#   }],
# ... (truncated)
# }}
```

print_bma_motif_vs *Prints BMA motifs to the screen from a sequence of nodes*

Description

The motifs can be copy-pasted into a BMA canvas.

Usage

```
print_bma_motif_vs(node_seq, G)
```

Arguments

node_seq An igraph node sequence.
 G An igraph graph object.

Value

Returns 'NULL'.

Examples

```
interactions <- import_omnipath_interactions(resources = 'ARN')
graph <- interaction_graph(interactions)
print_bma_motif_vs(
  igraph::all_shortest_paths(
    graph,
    from = 'ULK1',
    to = 'ATG13'
  )$res,
  graph
)
```

print_interactions *Print OmniPath interactions*

Description

Prints the interactions or enzyme-substrate relationships in a nice format.

Usage

```
print_interactions(interDF, writeRefs = FALSE)
```

Arguments

interDF data.frame with the interactions generated by any of the following functions:

- `import_omnipath_enzsub`
- `import_omnipath_interactions`
- `import_pathwayextra_interactions`
- `import_kinaseextra_interactions`
- `import_ligreextra_interactions`
- `import_post_translational_interactions`
- `import_dorothea_interactions`
- `import_tf_target_interactions`
- `import_transcriptional_interactions`
- `import_mirnatarget_interactions`
- `import_all_interactions`

writeRefs [FALSE] writes also the PubMed IDs if available

Value

Returns 'NULL'.

Examples

```
enzsub <- import_omnipath_enzsub()
print_interactions(head(enzsub))
print_interactions(tail(enzsub), writeRefs = TRUE)
print_interactions(
  dplyr::filter(
    enzsub,
    enzyme_genesymbol == 'MAP2K1',
    substrate_genesymbol == 'MAPK3'
  )
)

signor <- import_omnipath_interactions(resources = 'SIGNOR')
print_interactions(head(signor))
#           source interaction          target n_resources
# 6 MAPK14 (Q16539) ==(+)==> MAPKAPK2 (P49137)         23
# 4 TRPM7 (Q96QT4) ==(+)==> ANXA1 (P04083)         10
# 1 PRKG1 (Q13976) ==(-)==> TRPC3 (Q13507)          8
# 2 PTPN1 (P18031) ==(-)==> TRPV6 (Q9H1D0)          6
# 5 PRKACA (P17612) ==(-)==> MCOLN1 (Q9GZU1)         6
# 3 RACK1 (P63244) ==(-)==> TRPM6 (Q9BX84)          2
```

print_path_es

Prints network paths in an edge sequence

Description

Pretty prints the interactions in a path.

Usage

```
print_path_es(edgeSeq, G)
```

Arguments

edgeSeq	edge sequence
G	igraph object (from ptms or any interaction dataset)

Value

Returns 'NULL'.

See Also

- [print_path_vs](#)

Examples

```
interactions <- import_omnipath_interactions(resources = c('Signalink3'))
OPI_g <- interaction_graph(interactions = interactions)
print_path_es(
  suppressWarnings(igraph::shortest_paths(
    OPI_g,
```

```

        from = 'TYR03',
        to = 'STAT3',
        output = 'epath'
    ))$path[[1]],
    OPI_g
)

```

print_path_vs *Print networks paths given by node sequence*

Description

Prints the interactions in the path in a nice format.

Usage

```
print_path_vs(nodeSeq, G)
```

Arguments

nodeSeq	node sequence
G	igraph object (from ptms or interactions)

Value

Returns 'NULL'.

See Also

[print_path_es](#)

Examples

```

interactions <- import_omnipath_interactions(resources=c('Signalink3'))
OPI_g <- interaction_graph(interactions = interactions)
print_path_vs(
  igraph::all_shortest_paths(
    OPI_g,
    from = 'TYR03',
    to = 'STAT3'
  )$vpath,
  OPI_g
)
enzsub <- import_omnipath_enzsub(resources=c('PhosphoSite', 'SIGNOR'))
enzsub_g <- enzsub_graph(enzsub)
print_path_vs(
  igraph::all_shortest_paths(
    enzsub_g,
    from = 'SRC',
    to = 'STAT1'
  )$res,
  enzsub_g
)

```

ramilowski_download *Downloads ligand-receptor interactions from Ramilowski et al. 2015*

Description

Curated ligand-receptor pairs from Supplementary Table 2 of the article "A draft network of ligand-receptor mediated multicellular signaling in human" (<https://www.nature.com/articles/ncomms8866>).

Usage

```
ramilowski_download()
```

Value

A data frame (tibble) with interactions.

Examples

```
rami_interactions <- ramilowski_download()
rami_interactions
# # A tibble: 2,557 x 16
#   Pair.Name Ligand.Approved. Ligand.Name Receptor.Approv.
#   <chr>      <chr>                <chr>      <chr>
# 1 A2M_LRP1  A2M                        alpha-2-ma. LRP1
# 2 AANAT_MT. AANAT                      aralkylami. MTNR1A
# 3 AANAT_MT. AANAT                      aralkylami. MTNR1B
# 4 ACE_AGTR2 ACE                       angiotensi. AGTR2
# 5 ACE_BDKR. ACE                       angiotensi. BDKRB2
# # . with 2,547 more rows, and 12 more variables: Receptor.Name <chr>,
# #   DLRP <chr>, HPMR <chr>, IUPHAR <chr>, HPRD <chr>,
# #   STRING.binding <chr>, STRING.experiment <chr>, HPMR.Ligand <chr>,
# #   HPMR.Receptor <chr>, PMID.Manual <chr>, Pair.Source <chr>,
# #   Pair.Evidence <chr>
```

regnetwork_directions *Transcription factor effects from RegNetwork*

Description

Transcription factor effects from RegNetwork

Usage

```
regnetwork_directions(organism = "human")
```

Arguments

organism Character: either human or mouse.

Value

A data frame (tibble) of TF-target interactions with effect signs.

Examples

```
regn_dir <- regnetwork_directions()
regn_dir
# # A tibble: 3,954 x 5
#   source_genesymb. source_entrez target_genesymb. target_entrez
#   <chr>           <chr>           <chr>           <chr>
# 1 AHR             196             CDKN1B          1027
# 2 APLNR           187             PIK3C3          5289
# 3 APLNR           187             PIK3R4          30849
# 4 AR              367             KLK3            354
# 5 ARNT            405             ALDOA           226
# # . with 3,944 more rows, and 1 more variable: effect <dbl>
```

regnetwork_download *Interactions from RegNetwork*

Description

Downloads transcriptional and post-transcriptional regulatory interactions from the RegNetwork database (<http://www.regnetworkweb.org/>). The information about effect signs (stimulation or inhibition), provided by `regnetwork_directions` are included in the result.

Usage

```
regnetwork_download(organism = "human")
```

Arguments

`organism` Character: either human or mouse.

Value

Data frame with interactions.

Examples

```
regn_interactions <- regnetwork_download()
regn_interactions
# # A tibble: 372,778 x 7
#   source_genesymb. source_entrez target_genesymb. target_entrez
#   <chr>           <chr>           <chr>           <chr>
# 1 USF1            7391            S100A6          6277
# 2 USF1            7391            DUSP1           1843
# 3 USF1            7391            C4A             720
# 4 USF1            7391            ABCA1           19
# 5 TP53            7157            TP73            7161
# # . with 372,768 more rows, and 3 more variables: effect <dbl>,
# #   source_type <chr>, target_type <chr>
```

`relations_list_to_table`*Table from a nested list of ontology relations*

Description

Converting the nested list to a table is a more costly operation, it takes a few seconds. Best to do it only once, or pass `tables = TRUE` to `obo_parser`, and convert the data frame to list, if you also need it in list format.

Usage

```
relations_list_to_table(relations, direction = NULL)
```

Arguments

<code>relations</code>	A nested list of ontology relations (the "relations" element of the list returned by <code>obo_parser</code> in case its argument 'tables' is FALSE).
<code>direction</code>	Override the direction (i.e. child -> parents or parent -> children). The nested lists produced by functions in the current package add an attribute "direction" thus no need to pass this value. If the attribute and the argument are both missing, the column will be named simply "side2" and it won't be clear whether the relations point from "term" to "side2" or the other way around. The direction should be a character vector of length 2 with the values "parents" and "children".

Value

The relations converted to a data frame (tibble).

See Also

- [swap_relations](#)
- [relations_table_to_list](#)
- [obo_parser](#)

Examples

```
goslim_url <-  
  "http://current.geneontology.org/ontology/subsets/goslim_generic.obo"  
path <- tempfile()  
httr::GET(goslim_url, httr::write_disk(path, overwrite = TRUE))  
obo <- obo_parser(path, tables = FALSE)  
unlink(path)  
rel_tbl <- relations_list_to_table(obo$relations)
```

`relations_table_to_graph`*Graph from a table of ontology relations*

Description

Graph from a table of ontology relations

Usage

```
relations_table_to_graph(relations)
```

Arguments

`relations` A data frame of ontology relations (the "relations" element of the list returned by `obo_parser` in case its argument 'tables' is TRUE).

Details

By default the relations point from child to parents, the edges in the graph will be of the same direction. Use `swap_relations` on the data frame to reverse the direction.

Value

The relations converted to an igraph graph object.

Examples

```
go <- get_db('go_basic')
go_graph <- relations_table_to_graph(go$relations)
```

`relations_table_to_list`*Nested list from a table of ontology relations*

Description

Nested list from a table of ontology relations

Usage

```
relations_table_to_list(relations)
```

Arguments

`relations` A data frame of ontology relations (the "relations" element of the list returned by `obo_parser` in case its argument 'tables' is TRUE).

Value

The relations converted to a nested list.

See Also

- [relations_list_to_table](#)
- [swap_relations](#)
- [obo_parser](#)

Examples

```
goslim_url <-  
  "http://current.geneontology.org/ontology/subsets/goslim_generic.obo"  
path <- tempfile()  
httr::GET(goslim_url, httr::write_disk(path, overwrite = TRUE))  
obo <- obo_parser(path, tables = TRUE)  
unlink(path)  
rel_list <- relations_table_to_list(obo$relations)
```

remap_dorothea_download

Downloads TF-target interactions from ReMap

Description

ReMap (<http://remap.univ-amu.fr/>) is a database of ChIP-Seq experiments. It provides raw and merged peaks and CRMs (cis regulatory motifs) with their associations to regulators (TFs). TF-target relationships can be derived as it is written in Garcia-Alonso et al. 2019: "For ChIP-seq, we downloaded the binding peaks from ReMap and scored the interactions between each TF and each gene according to the distance between the TFBSs and the genes' transcription start sites. We evaluated different filtering strategies that consisted of selecting only the top-scoring 100, 200, 500, and 1000 target genes for each TF." (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6673718/#s1title>). This function returns the top TF-target relationships as used in DoRothea: https://github.com/saezlab/dorothea/blob/master/inst/scripts/02_chip_seq.R).

Usage

```
remap_dorothea_download()
```

Value

Data frame with TF-target relationships.

See Also

[remap_tf_target_download](#)

Examples

```

remap_interactions <- remap_dorothea_download()
remap_interactions
# # A tibble: 136,988 x 2
#   tf      target
#   <chr> <chr>
# 1 ADNP  ABCC1
# 2 ADNP  ABCC6
# 3 ADNP  ABHD5
# 4 ADNP  ABT1
# 5 ADNP  AC002066.1
# # . with 136,978 more rows

```

remap_filtered

Downloads TF-target interactions from ReMap

Description

Downloads the ReMap TF-target interactions as processed by Garcia-Alonso et al. (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6673718/#s1title>) and filters them based on a score threshold, the top targets and whether the TF is included in the TF census (Vaquerizas et al. 2009). The code for filtering is adapted from DoRothEA, written by Christian Holland.

Usage

```
remap_filtered(score = 100, top_targets = 500, only_known_tfs = TRUE)
```

Arguments

score	Numeric: a minimum score between 0 and 1000, records with lower scores will be excluded. If NULL no filtering performed.
top_targets	Numeric: the number of top scoring targets for each TF. Essentially the maximum number of targets per TF. If NULL the number of targets is not restricted.
only_known_tfs	Logical: whether to exclude TFs which are not in TF census.

Value

Data frame with TF-target relationships.

See Also

- [remap_tf_target_download](#)
- [remap_filtered](#)
- [tfcensus_download](#)

Examples

```
remap_interactions <- remap_filtered()
nrow(remap_interactions)
# [1] 145680

remap_interactions <- remap_filtered(top_targets = 100)
remap_interactions
# # A tibble: 30,330 x 2
#   source_genesymbol target_genesymbol
#   <chr>              <chr>
# 1 ADNP                ABCC1
# 2 ADNP                ABT1
# 3 ADNP                AC006076.1
# 4 ADNP                AC007792.1
# 5 ADNP                AC011288.2
# # . with 30,320 more rows
```

remap_tf_target_download

Downloads TF-target interactions from ReMap

Description

ReMap (<http://remap.univ-amu.fr/>) is a database of ChIP-Seq experiments. It provides raw and merged peaks and CRMs (cis regulatory motifs) with their associations to regulators (TFs). TF-target relationships can be derived as it is written in Garcia-Alonso et al. 2019: "For ChIP-seq, we downloaded the binding peaks from ReMap and scored the interactions between each TF and each gene according to the distance between the TFBSs and the genes' transcription start sites. We evaluated different filtering strategies that consisted of selecting only the top-scoring 100, 200, 500, and 1000 target genes for each TF." (<https://www.ncbi.nlm.nih.gov/pmc/articles/PMC6673718/#s1title>). This function retrieves the full processed TF-target list from the data deposited in <https://zenodo.org/record/3713238>.

Usage

```
remap_tf_target_download()
```

Value

Data frame with TF-target relationships.

See Also

- [remap_dorothea_download](#)
- [remap_filtered](#)

Examples

```

remap_interactions <- remap_tf_target_download()
remap_interactions
# # A tibble: 9,546,470 x 4
#   source_genesymbol target_genesymbol target_ensembl   score
#   <chr>             <chr>             <chr>             <dbl>
# 1 ADNP              PTPRS              ENSG00000105426.16 1000
# 2 AFF4              PRKCH              ENSG00000027075.14 1000
# 3 AHR               CTNND2             ENSG00000169862.18 1000
# 4 AR                PDE4D              ENSG00000113448.18 1000
# 5 ARID1A           PLEC               ENSG00000178209.14 1000
# # . with 9,546,460 more rows

```

resources_colname	<i>Name of the column with the resources</i>
-------------------	--

Description

Unfortunately the column title is different across the various query types in the OmniPath web service, so we need to guess.

Usage

```
resources_colname(data)
```

Arguments

data A data frame downloaded by any `import_...` function in the current package.

Value

Character: the name of the column, if any of the column names matches.

Examples

```

co <- import_omnipath_complexes()
resources_colname(co)
# [1] "sources"

```

simplify_intercell_network
Simplify an intercell network

Description

The intercellular communication network data frames, created by [import_intercell_network](#), are combinations of a network data frame with two copies of the intercell annotation data frames, all of them already having quite some columns. Here we keep only the names of the interacting pair, their intercellular communication roles, and the minimal information of the origin of both the interaction and the annotations. Optionally further columns can be selected.

Usage

```
simplify_intercell_network(network, ...)
```

Arguments

network	An intercell network data frame, as provided by import_intercell_network .
...	Optional, further columns to select.

Value

An intercell network data frame with some columns removed.

See Also

- [import_intercell_network](#)
- [unique_intercell_network](#)
- [filter_intercell_network](#)

Examples

```
icn <- import_intercell_network()  
icn_s <- simplify_intercell_network(icn)
```

swap_relations *Reverse the direction of ontology relations*

Description

Reverse the direction of ontology relations

Usage

```
swap_relations(relations)
```

Arguments

`relations` The ‘relations’ component of the data returned by `obo_parser` or any ‘...ontology_download’ function such as `go_ontology_download`. Depending on the `tables` argument of those functions the ‘relations’ can be a data frame or a nested list.

Value

Same type as the input, but the relations swapped: if in the input these pointed from each child to the parents, in the output they point from each parent to their children, and vice versa.

See Also

- [relations_list_to_table](#)
- [relations_table_to_list](#)
- [obo_parser](#)

Examples

```
goslim_url <-  
  "http://current.geneontology.org/ontology/subsets/goslim_generic.obo"  
path <- tempfile()  
httr::GET(goslim_url, httr::write_disk(path, overwrite = TRUE))  
obo <- obo_parser(path)  
unlink(path)  
rel_swapped <- swap_relations(obo$relations)
```

`tfcensus_download` *Downloads the list of transcription factors from TF census*

Description

Vaquerizas et al. published in 2009 a list of transcription factors. This function retrieves Supplementary Table 2 from the article (<http://www.nature.com/nrg/journal/v10/n4/index.html>).

Usage

```
tfcensus_download()
```

Value

A data frame (tibble) listing transcription factors.

Examples

```
tfcensus <- tfcensus_download()
tfcensus
# # A tibble: 1,987 x 7
#   Class `Ensembl ID` `IPI ID` `Interpro DBD` `Interpro DNA-b.
#   <chr> <chr> <chr> <chr> <chr>
# 1 a ENSG000000000. IPI0021. NA IPR001289
# 2 a ENSG000000000. IPI0004. IPR000047;IPR. NA
# 3 a ENSG000000000. IPI0001. IPR001356;IPR. NA
# 4 a ENSG000000000. IPI0029. IPR000910;IPR. NA
# 5 a ENSG000000000. IPI0001. IPR007087;IPR. IPR006794
# # . with 1,977 more rows, and 2 more variables: `HGNC symbol` <chr>,
# # `Tissue-specificity` <chr>
```

translate_ids

*Translate gene and protein identifiers***Description**

Translates a vector of identifiers, resulting a new vector, or a column of identifiers in a data frame by creating another column with the target identifiers.

Usage

```
translate_ids(
  d,
  ...,
  uploadlists = FALSE,
  keep_untranslated = TRUE,
  return_df = FALSE,
  organism = 9606,
  reviewed = TRUE
)
```

Arguments

d	Character vector or data frame.
...	At least two arguments, with or without names. The first of these arguments describes the source identifier, the rest of them describe the target identifier(s). The values of all these arguments must be valid identifier types as shown in Details. The names of the arguments are column names. In case of the first (source) ID the column must exist. For the rest of the IDs new columns will be created with the desired names. For ID types provided as arguments without names, the name of the ID type will be used for column name.
uploadlists	Force using the uploadlists service from UniProt. By default the plain query interface is used (implemented in uniprot_full_id_mapping_table in this package). If any of the provided ID types is only available in the uploadlists service, it will be automatically selected. The plain query interface is preferred because in the long term, with caching, it requires less download and data storage.

keep_untranslated	In case the output is a data frame, keep the records where the source identifier could not be translated. At these records the target identifier will be NA.
return_df	Return a data frame even if the input is a vector.
organism	Integer, NCBI Taxonomy ID of the organism (by default 9606 for human). Matters only if uploadlists is FALSE.
reviewed	Translate only reviewed (TRUE), only unreviewed (FALSE) or both (NULL) UniProt records. Matters only if uploadlists is FALSE.

Details

This function, depending on the `uploadlists` parameter, uses either the `uploadlists` service of UniProt or plain UniProt queries to obtain identifier translation tables. The possible values for `from` and `to` are the identifier type abbreviations used in the UniProt API, please refer to the table here: https://www.uniprot.org/help/api_idmapping. In addition, simple synonyms are available which realize a uniform API for the `uploadlists` and UniProt query based backends. These are the followings:

OmnipathR	Uploadlists	UniProt query
uniprot	ACC	id
uniprot_entry	ID	entry name
genesymbol	GENENAME	genes(PREFERRED)
genesymbol_syn		genes(ALTERNATIVE)
hgnc	HGNC_ID	database(HGNC)
entrez	P_ENTREZGENEID	database(geneid)
ensg	ENSEMBLGENOME_ID	
enst	ENSEMBL_TRS_ID	database(ensembl)
ensp	ENSEMBL_PRO_ID	
ensgt	ENSEMBLGENOME_TRS_ID	
ensgp	ENSEMBLGENOME_PRO_ID	
ensembl	ENSEMBL_ID	
protein_name		protein names
refseqp	P_REFSEQ_AC	database(refseq)
refseqn	REFSEQ_NT_ID	
embl	EMBL	database(embl)
embl_id	EMBL_ID	
gi	P_GI	
pir	PIR	
pdb	PDB_ID	

The mapping between identifiers can be ambiguous. In this case one row in the original data frame yields multiple rows or elements in the returned data frame or vector(s).

Value

- Data frame: if the input is a data frame or the input is a vector and `return_df` is TRUE.
- Vector: if the input is a vector, there is only one target ID type and `return_df` is FALSE.
- List of vectors: if the input is a vector, there are more than one target ID types and `return_df` is FALSE. The names of the list will be ID types (as they were column names, see the description of the `...` argument), and the list will also include the source IDs.

See Also

- [uniprot_id_mapping_table](#)
- [uniprot_full_id_mapping_table](#)

Examples

```
d <- data.frame(uniprot_id = c('P00533', 'Q9ULV1', 'P43897', 'Q9Y2P5'))
d <- translate_ids(d, uniprot_id = uniprot, genesymbol)
d
#   uniprot_id genesymbol
# 1   P00533      EGFR
# 2   Q9ULV1      FZD4
# 3   P43897      TSFM
# 4   Q9Y2P5     SLC27A5
```

trrust_download

*Downloads TF-target interactions from TRRUST***Description**

TRRUST v2 (<https://www.grnpedia.org/trrust/>) is a database of literature mined TF-target interactions for human and mouse.

Usage

```
trrust_download(organism = "human")
```

Arguments

organism Character: either "human" or "mouse".

Value

A data frame of TF-target interactions.

Examples

```
trrust_interactions <- trrust_download()
trrust_interactions
# # A tibble: 11,698 x 4
#   source_genesymbol target_genesymbol effect reference
#   <chr>             <chr>             <dbl> <chr>
# 1 AATF              BAX                 -1 22909821
# 2 AATF              CDKN1A              0 17157788
# 3 AATF              KLK3                0 23146908
# 4 AATF              MYC                 1 20549547
# 5 AATF              TP53                0 17157788
# 6 ABL1              BAX                 1 11753601
# 7 ABL1              BCL2               -1 11753601
# # . with 11,688 more rows
```

 uniprot_full_id_mapping_table

Creates an ID translation table from UniProt data

Description

Creates an ID translation table from UniProt data

Usage

```
uniprot_full_id_mapping_table(
  to,
  from = "id",
  reviewed = TRUE,
  organism = 9606
)
```

Arguments

to	Character or symbol: target ID type. See Details for possible values.
from	Character or symbol: source ID type. See Details for possible values.
reviewed	Translate only reviewed (TRUE), only unreviewed (FALSE) or both (NULL) UniProt records.
organism	Integer, NCBI Taxonomy ID of the organism (by default 9606 for human).

Details

For both source and target ID type, this function accepts column codes used by UniProt and some simple shortcuts defined here. For the UniProt codes please refer to <https://www.uniprot.org/help/uniprotkb>. The shortcuts are `entrez`, `genesymbol`, `genesymbol_syn` (synonym gene symbols), `hgnc`, `embl`, `refseqp` (RefSeq protein), `enst` (Ensembl transcript), `uniprot_entry` (UniProtKB AC, e.g. EGFR_HUMAN), `protein_name` (full name of the protein), `uniprot` (UniProtKB ID, e.g. P00533). For a complete table please refer to [translate_ids](#).

Value

A data frame (tibble) with columns 'From' and 'To', UniProt IDs and the corresponding foreign IDs, respectively.

See Also

[translate_ids](#)

Examples

```
uniprot_entrez <- uniprot_full_id_mapping_table(to = 'entrez')
uniprot_entrez
# # A tibble: 20,723 x 2
#   From To
#   <chr> <chr>
# 1 Q96R72 NA
```



```
# 2 Q9UKL2 23538
# 3 Q9H205 144125
# 4 Q8NGN2 219873
# 5 Q8NGC1 390439
# # . with 20,713 more rows
```

uniprot_id_mapping_table

Retrieves an identifier translation table from the UniProt uploadlists service

Description

Retrieves an identifier translation table from the UniProt uploadlists service

Usage

```
uniprot_id_mapping_table(identifiers, from, to, chunk_size = 5000)
```

Arguments

identifiers	Character vector of identifiers
from	Character or symbol: type of the identifiers provided. See Details for possible values.
to	Character or symbol: identifier type to be retrieved from UniProt. See Details for possible values.
chunk_size	Integer: query the identifiers in chunks of this size. If you are experiencing download failures, try lower values.

Details

This function uses the uploadlists service of UniProt to obtain identifier translation tables. The possible values for ‘from’ and ‘to’ are the identifier type abbreviations used in the UniProt API, please refer to the table here: https://www.uniprot.org/help/api_idmapping or the table of synonyms supported by the current package: [translate_ids](#). Note: if the number of identifiers is larger than the chunk size the log message about the cache origin is not guaranteed to be correct (most of the times it is still correct).

Value

A data frame (tibble) with columns ‘From’ and ‘To’, the identifiers provided and the corresponding target IDs, respectively.

See Also

[translate_ids](#)

Examples

```
uniprot_genesymbol <- uniprot_id_mapping_table(
  c('P00533', 'P23771'), uniprot, genesymbol
)
uniprot_genesymbol
# # A tibble: 2 x 2
#   From To
#   <chr> <chr>
# 1 P00533 EGFR
# 2 P23771 GATA3
```

unique_intercell_network

Unique intercellular interactions

Description

In the intercellular network data frames produced by [import_intercell_network](#), by default each pair of annotations for an interaction is represented in a separate row. This function drops the annotations and keeps only the distinct interacting pairs.

Usage

```
unique_intercell_network(network, ...)
```

Arguments

network	An intercellular network data frame as produced by import_intercell_network .
...	Additional columns to keep. Note: if these have multiple values for an interacting pair, only the first row will be preserved.

Value

A data frame with interacting pairs and interaction attributes.

See Also

- [import_intercell_network](#)
- [simplify_intercell_network](#)
- [filter_intercell_network](#)

Examples

```
icn <- import_intercell_network()
icn_unique <- unique_intercell_network(icn)
```

 vinayagam_download *Protein-protein interactions from Vinayagam 2011*

Description

Retrieves the Supplementary Table S6 from Vinayagam et al. 2011. Find out more at <https://doi.org/10.1126/scisignal.2001699>.

Usage

```
vinayagam_download()
```

Value

A data frame (tibble) with interactions.

Examples

```
vinayagam_interactions <- vinayagam_download()
vinayagam_interactions
# # A tibble: 34,814 x 5
#   `Input-node Gen. `Input-node Gen. `Output-node Ge. `Output-node Ge.
#   <chr>                <dbl> <chr>                <dbl>
# 1 C1orf103              55791 MNAT1              4331
# 2 MAST2                 23139 DYNLL1              8655
# 3 RAB22A                57403 APPL2             55198
# 4 TRAP1                 10131 EXT2               2132
# 5 STAT2                 6773  COPS4              51138
# # . with 34,804 more rows, and 1 more variable:
# # `Edge direction score` <dbl>
```

 walk_ontology_tree *All nodes of a subtree starting from the selected nodes*

Description

Starting from the selected nodes, recursively walks the ontology tree until it reaches either the root or leaf nodes. Collects all visited nodes.

Usage

```
walk_ontology_tree(
  terms,
  ancestors = TRUE,
  db_key = "go_basic",
  ids = TRUE,
  method = "gra",
  relations = c("is_a", "part_of", "occurs_in", "regulates", "positively_regulates",
    "negatively_regulates")
)
```

Arguments

terms	Character vector of ontology term IDs or names. A mixture of IDs and names can be provided.
ancestors	Logical: if FALSE the ontology tree is traversed towards the leaf nodes; if TRUE, the tree is traversed until the root. The former returns the ancestors (parents), the latter the descendants (children).
db_key	Character: key to identify the ontology database. For the available keys see omnipath_show_db .
ids	Logical: whether to return IDs or term names.
method	Character: either "gra" or "lst". The implementation to use for traversing the ontology tree. The graph based implementation is faster than the list based, the latter will be removed in the future.
relations	Character vector of ontology relation types. Only these relations will be used.

Details

Note: this function relies on the database manager, the first call might take long because of the database load process. Subsequent calls within a short period should be faster. See [get_ontology_db](#).

Value

Character vector of ontology IDs. If the input terms are all leaves or roots NULL is returned. The starting nodes won't be included in the result unless they fall onto the traversal path from other nodes.

See Also

- [omnipath_show_db](#)
- [get_ontology_db](#)

Examples

```
walk_ontology_tree(c('GO:0006241', 'GO:0044211'))
# [1] "GO:0006139" "GO:0006220" "GO:0006221" "GO:0006241" "GO:0006725"
# [6] "GO:0006753" "GO:0006793" "GO:0006796" "GO:0006807" "GO:0008150"
# ... (truncated)
walk_ontology_tree(c('GO:0006241', 'GO:0044211'), ancestors = FALSE)
# [1] "GO:0044210" "GO:0044211"
walk_ontology_tree(
  c('GO:0006241', 'GO:0044211'),
  ancestors = FALSE,
  ids = FALSE
)
# [1] "'de novo' CTP biosynthetic process" "CTP salvage"
```

zenodo_download	<i>Retrieves data from Zenodo</i>
-----------------	-----------------------------------

Description

Zenodo is a repository of large scientific datasets. Many projects and publications make their datasets available at Zenodo. This function downloads an archive from Zenodo and extracts the requested file.

Usage

```
zenodo_download(
  path,
  reader = NULL,
  reader_param = list(),
  url_key = NULL,
  zenodo_record = NULL,
  zenodo_fname = NULL,
  url_param = list(),
  url_key_param = list(),
  ...
)
```

Arguments

path	Character: path to the file within the archive.
reader	Optional, a function to read the connection.
reader_param	List: arguments for the reader function.
url_key	Character: name of the option containing the URL
zenodo_record	The Zenodo record ID, either integer or character.
zenodo_fname	The file name within the record.
url_param	List: variables to insert into the URL string (which is returned from the options).
url_key_param	List: variables to insert into the 'url_key'.
...	Passed to archive_extractor

Value

A connection

Examples

```
# an example from the OmnipathR::remap_tf_target_download function:
remap_dorothea <- zenodo_download(
  zenodo_record = 3713238,
  zenodo_fname = 'tf_target_sources.zip',
  path = (
    'tf_target_sources/chip_seq/remap/gene_tf_pairs_genesymbol.txt'
  ),
  reader = read_tsv,
  reader_param = list(
```

```
col_names = c(
  'source_genesymbol',
  'target_genesymbol',
  'target_ensembl',
  'score'
),
col_types = cols(),
progress = FALSE
),
resource = 'ReMap'
)
```

Index

* datasets

.omnipath_options_defaults, 6
.omnipath_options_defaults, 6

all_uniprots, 6
ancestors, 7
annotated_network, 8
annotation_categories, 9

bioplex1, 9, 10–13
bioplex2, 10, 10, 11–13
bioplex3, 10, 11, 12, 13
bioplex_all, 10, 11, 11, 13
bioplex_hct116_1, 10–12, 12
bma_motif_es, 13
bma_motif_vs, 14

consensuspathdb_download, 14, 93
consensuspathdb_raw_table, 15

descendants, 16

enzsub_graph, 17, 22, 50
evex_download, 17, 73, 94

filter_by_resource, 18
filter_intercell_network, 19, 41, 42, 83,
84, 87, 89, 139, 146
filter_sources (filter_by_resource), 18
find_all_paths, 17, 21, 61

get_annotation_databases, 48
get_annotation_databases
(get_annotation_resources), 22
get_annotation_resources, 8, 22, 47
get_complex_genes, 23
get_complex_resources, 24
get_complexes_databases, 48
get_complexes_databases
(get_complex_resources), 24
get_db, 24, 29, 33, 70
get_enzsub_resources, 25, 50
get_interaction_databases
(get_interaction_resources), 26

get_interaction_resources, 26, 37–39,
43–47, 50, 51, 54–59
get_intercell_categories, 27, 27, 42, 52,
53
get_intercell_classes
(get_intercell_generic_categories),
27
get_intercell_generic_categories, 27,
27, 42, 53
get_intercell_resources, 28, 52
get_ontology_db, 7, 16, 28, 148
get_ptms_databases, 49
get_ptms_databases
(get_enzsub_resources), 25
get_resources, 22, 24–26, 28, 29
get_signed_ptms, 30
giant_component, 17, 22, 30, 61
go_annot_download, 31, 33
go_annot_slim, 31, 32
go_ontology_download, 33, 33, 140
guide2pharma_download, 34, 84

harmonizome_download, 35, 74
hpo_download, 35
htridb_download, 36, 75

import_all_interactions, 26, 37, 39,
43–45, 47, 51, 54–57, 59, 61, 128
import_AllInteractions
(import_all_interactions), 37
import_dorothea_interactions, 26, 38, 61,
128
import_intercell_network, 8, 19, 21, 39,
53, 84, 139, 146
import_KinaseExtra_Interactions
(import_kinaseextra_interactions),
42
import_kinaseextra_interactions, 26, 40,
42, 42, 60, 61, 128
import_LigrecExtra_Interactions
(import_ligrecextra_interactions),
43
import_ligrecextra_interactions, 26, 40,
42, 43, 60, 61, 128

- `import_lncrna_mrna_interactions`, 45
- `import_miRNAtarget_Interactions`
(`import_mirnatarget_interactions`), 46
- `import_mirnatarget_interactions`, 26, 46, 61, 128
- `import_OmniPath_annotations`
(`import_omnipath_annotations`), 47
- `import_Omnipath_annotations`
(`import_omnipath_annotations`), 47
- `import_omnipath_annotations`, 22, 47, 125, 126
- `import_OmniPath_complexes`
(`import_omnipath_complexes`), 48
- `import_Omnipath_complexes`
(`import_omnipath_complexes`), 48
- `import_omnipath_complexes`, 23, 24, 48
- `import_omnipath_enzsub`, 17, 25, 30, 49, 60, 128
- `import_OmniPath_Interactions`
(`import_omnipath_interactions`), 50
- `import_Omnipath_Interactions`
(`import_omnipath_interactions`), 50
- `import_omnipath_interactions`, 8, 26, 30, 39, 40, 42, 50, 50, 60, 61, 128
- `import_OmniPath_intercell`
(`import_omnipath_intercell`), 51
- `import_Omnipath_intercell`
(`import_omnipath_intercell`), 51
- `import_omnipath_intercell`, 27, 28, 39, 40, 42, 51, 62
- `import_OmniPath_PTMS`
(`import_omnipath_enzsub`), 49
- `import_Omnipath_PTMS`
(`import_omnipath_enzsub`), 49
- `import_PathwayExtra_Interactions`
(`import_pathwayextra_interactions`), 53
- `import_pathwayextra_interactions`, 26, 40, 42, 53, 60, 61, 128
- `import_post_translational_interactions`, 54, 60, 96, 128
- `import_tf_mirna_interactions`, 55
- `import_tf_target_interactions`, 57, 61, 128
- `import_TFregulons_Interactions`
(`import_dorothea_interactions`), 38
- `import_tfregulons_interactions`
(`import_dorothea_interactions`), 38
- `import_transcriptional_interactions`, 58, 61, 75, 128
- `inbiomap_download`, 59, 60, 95
- `inbiomap_raw`, 59, 60
- `interaction_graph`, 22, 38, 39, 43–45, 47, 51, 54–57, 59, 60
- `intercell_categories`, 61
- `intercell_consensus_filter`, 53, 62
- `is_ontology_id`, 63
- `kegg_info`, 63, 64, 67, 68
- `kegg_open`, 64, 64, 67, 68
- `kegg_pathway_download`, 65, 66, 67, 69
- `kegg_pathway_list`, 63–66, 67, 68, 69
- `kegg_pathways_download`, 65, 66, 67, 69
- `kegg_picture`, 64, 67, 68
- `kegg_process`, 65–67, 68
- `load_db`, 69
- `nichenet_build_model`, 70, 82
- `nichenet_expression_data`, 71, 90
- `nichenet_gr_network`, 72, 73–78, 87–89
- `nichenet_gr_network_evex`, 72, 73, 76
- `nichenet_gr_network_harmonizome`, 72, 74, 76
- `nichenet_gr_network_htridb`, 72, 75, 76
- `nichenet_gr_network_omnipath`, 72, 75, 76
- `nichenet_gr_network_pathwaycommons`, 72, 76, 76
- `nichenet_gr_network_regnetwork`, 72, 76, 77
- `nichenet_gr_network_remap`, 72, 76, 77
- `nichenet_gr_network_trrust`, 72, 76, 78
- `nichenet_ligand_activities`, 79
- `nichenet_ligand_target_links`, 80
- `nichenet_ligand_target_matrix`, 79, 80, 81
- `nichenet_lr_network`, 79, 82, 82, 84, 85, 87–90
- `nichenet_lr_network_guide2pharma`, 83, 83
- `nichenet_lr_network_omnipath`, 75, 83, 84, 84, 95
- `nichenet_lr_network_ramilowski`, 83, 85
- `nichenet_main`, 85, 98
- `nichenet_networks`, 70, 87, 88, 90
- `nichenet_optimization`, 70, 89
- `nichenet_remove_orphan_ligands`, 90
- `nichenet_results_dir`, 87, 91

- nichenet_signaling_network, 86–89, 91, 93–96
- nichenet_signaling_network_cpdb, 92, 93
- nichenet_signaling_network_evex, 92, 93
- nichenet_signaling_network_harmonizome, 92, 94
- nichenet_signaling_network_inbiomap, 92, 95
- nichenet_signaling_network_omnipath, 92, 95
- nichenet_signaling_network_pathwaycommons, 92, 96
- nichenet_signaling_network_vinayagam, 92, 97
- nichenet_test, 87, 97
- nichenet_workarounds, 87, 98

- obo_parser, 99, 133–135, 140
- omnipath_cache_autoclean, 101, 110
- omnipath_cache_clean, 101, 102, 110
- omnipath_cache_clean_db, 102
- omnipath_cache_download_ready, 103
- omnipath_cache_filter_versions, 103
- omnipath_cache_get, 104, 106
- omnipath_cache_key, 105
- omnipath_cache_latest_or_new, 106
- omnipath_cache_latest_version, 107
- omnipath_cache_load, 107
- omnipath_cache_move_in, 108, 112
- omnipath_cache_remove, 101, 110, 114
- omnipath_cache_save, 108, 109, 111
- omnipath_cache_search, 112
- omnipath_cache_set_ext, 113
- omnipath_cache_update_status, 113
- omnipath_cache_wipe, 110, 114
- omnipath_get_config_path, 115, 118
- omnipath_load_config, 115, 118
- omnipath_log, 116, 117
- omnipath_logfile, 116, 117
- omnipath_msg, 117
- omnipath_reset_config, 118
- omnipath_save_config, 118, 119
- omnipath_set_cachedir, 119
- omnipath_set_console_loglevel, 120, 121
- omnipath_set_logfile_loglevel, 120, 121
- omnipath_set_loglevel, 121
- omnipath_show_db, 7, 16, 25, 28, 29, 70, 122, 123, 124, 148
- omnipath_unlock_cache_db, 122
- OmnipathR, 100
- ontology_ensure_id, 123
- ontology_ensure_name, 123
- ontology_name_id, 124

- pathwaycommons_download, 76, 125
- pivot_annotations, 47, 48, 125
- print_bma_motif_es, 126
- print_bma_motif_vs, 127
- print_interactions, 38, 39, 43–45, 47, 50, 51, 54–57, 59, 128
- print_path_es, 129, 130
- print_path_vs, 129, 130
- printPath_es (print_path_es), 129
- printPath_vs (print_path_vs), 130
- ptms_graph (enzsub_graph), 17

- ramilowski_download, 85, 131
- regnetwork_directions, 131, 132
- regnetwork_download, 77, 132
- relations_list_to_table, 99, 133, 135, 140
- relations_table_to_graph, 134
- relations_table_to_list, 99, 133, 134, 140
- remap_dorothea_download, 135, 137
- remap_filtered, 78, 136, 136, 137
- remap_tf_target_download, 135, 136, 137
- resources_colname, 138

- simplify_intercell_network, 21, 42, 139, 146
- swap_relations, 99, 133–135, 139

- tfcensus_download, 136, 140
- translate_ids, 141, 144, 145
- ttrust_download, 78, 143

- uniprot_full_id_mapping_table, 141, 143, 144
- uniprot_id_mapping_table, 143, 145
- unique_intercell_network, 20, 21, 41, 42, 139, 146

- vinayagam_download, 147
- walk_ontology_tree, 147

- zenodo_download, 149